



# MASTER GLASS LED candles and lustres



# MAS LEDCandleDT5.9-60W E14 927 B35 CL G

Featuring a classic heritage design, Classic filament LED Lamps combine the familiar shapes of incandescent candles and lustres with the benefits of the long-lasting LED technology. It is an idea product to provide customers with cosy atmosphere. The MASTER LED candles and lustres can be dimmed for different lumen level and also for the different colour temperature. MASTER Glass Led Bulbs deliver significant energy savings, offering even 30% more compared to normal LED. They provide excellent quality of light. By offering a lifetime of 25,000 hours, the lamps reduce maintenance costs.

#### **Product data**

| General Information              |                              |
|----------------------------------|------------------------------|
| Cap base                         | E14 [E14]                    |
| Nominal lifetime                 | 25,000 h                     |
| Switching Cycle                  | 20,000                       |
| Lighting Technology              | LED                          |
| Flux measurement reference       | Sphere                       |
| CE mark                          | Yes                          |
| EU RoHS compliant                | Yes                          |
|                                  |                              |
| Light Technical                  |                              |
| Colour Code                      | 922-927 [CCT of 2200K-2700K] |
| Luminous Flux                    | 806 lm                       |
| Colour designation               | Warm Glow (WG)               |
| Correlated Colour Temperature    | 2200 2700 K                  |
| Luminous efficacy (rated) (nom.) | 136 lm/W                     |
| Colour consistency               | <6                           |
| Colour rendering index (CRI)     | 90                           |
|                                  |                              |

| LLMF at end of nominal lifetime (nom.) | 70 %        |
|----------------------------------------|-------------|
| Flickering value (PstLM)               | 0.9         |
| Stroboscopic effect                    | 0.4         |
| Photobiological safety according to EN | RG0         |
| 62471                                  |             |
|                                        |             |
| Operating and Electrical               |             |
| Line Frequency                         | 50 to 60 Hz |
| Input frequency                        | 50 to 60 Hz |
| Power Consumption                      | 5.9 W       |
| Lamp current (nom.)                    | 40 mA       |
| Wattage equivalent                     | 60 W        |
| Starting time (nom.)                   | 0.5 s       |
| Warm-up time to 60% light              | 0.5 s       |
| Power Factor (Fraction)                | 0.6         |
| Voltage (nom.)                         | 220-240 V   |
|                                        |             |

LINE - to and of a control life time (come)


Datasheet, 2023, April 15 data subject to change

# **MASTER GLASS LED candles and lustres**

| Temperature                        |                            |
|------------------------------------|----------------------------|
| Ambient temperature range          | -20°C to 45°C              |
| T-Case maximum (nom.)              | 70 °C                      |
|                                    |                            |
| Controls and Dimming               |                            |
| Dimmable                           | Only with specific dimmers |
|                                    |                            |
| Mechanical and Housing             |                            |
| Lamp Finish                        | Clear                      |
| Bulb material                      | Glass                      |
| Bulb shape                         | B35 [B 35 mm]              |
|                                    |                            |
| Approval and Application           |                            |
| Energy Efficiency Class            | D                          |
| Energy consumption kWh/1,000 hours | 6 kWh                      |
| EPREL registration number          | 1109147                    |


| EyeComfort                        | Yes                                |
|-----------------------------------|------------------------------------|
|                                   |                                    |
| Product Data                      |                                    |
| Full EOC                          | 871951444957200                    |
| Order product name                | MAS LEDCandleDT5.9-60W E14 927 B35 |
|                                   | CL G                               |
| Order code                        | 44957200                           |
| SAP numerator – quantity per pack | 1                                  |
| Numerator – packs per outer box   | 10                                 |
| Material no. (12 NC)              | 929003013982                       |
| Full product name                 | MAS LEDCandleDT5.9-60W E14 927 B35 |
|                                   | CL G                               |
| EAN/UPC - Case                    | 8719514449589                      |
| EAN/UPC - Product/Case            | 8719514449572                      |

# Dimensional drawing




| Product                                 | D     | С     |
|-----------------------------------------|-------|-------|
| MAS LEDCandleDT5.9-60W E14 927 B35 CL G | 35 mm | 97 mm |

## Photometric data








General uniform lighting - MAS LEDCandleDT5.9-60W E14 927 B35 CL G


## **MASTER GLASS LED candles and lustres**


#### Photometric data



Spectral Power Distribution Colour - MAS LEDCandle DT5.9-60W E14 927  $\,$  B35 CL  $\,$  G

#### Lifetime





Life Expectancy Diagram - MAS LEDCandleDT5.9-60W E14 927 B35 CL G

Lumen Maintenance Diagram - MAS LEDCandleDT5.9-60W E14 927 B35 CL G



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.