



MASTER LEDtube Mains T5



MASTER LEDtube 1500mm UO 36W 830 T5

The new Philips Master LEDtube Mains T5 brings simplicity to your lighting project. You don't need to pay attention to the driver technology anymore. Thanks to a unique design, Philips MASTER LEDtube Mains T5 installs in luminaires operating on mains power connection. So simple to operate! . Perfectly safe, reliable & easy to install, the Philips MASTER LEDtube Mains T5 is the ideal alternative to standard fluorescent tubes to maximise value over lifetime with high energy savings and lower maintenance costs.

Product data

General Information	
Cap base	G5 [G5]
Nominal lifetime	50,000 h
Switching Cycle	200,000
Lighting Technology	LED
Flux measurement reference	Sphere
CE mark	Yes
EU RoHS compliant	Yes
Light Technical	
Colour Code	830 [CCT of 3000K]
Beam angle (nom.)	200 degree(s)
Luminous Flux	5,200 lm
Colour designation	White (WH)
Correlated Colour Temperature	3000 K
Luminous efficacy (rated) (nom.)	144.00 lm/W
Colour consistency	<6
Colour rendering index (CRI)	80


LLMF at end of nominal lifetime (nom.)	70 %
Flickering value (PstLM)	1
Stroboscopic effect	0.4
Photobiological safety according to EN 62471 RGO	
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input frequency	50 to 60 Hz
Power Consumption	36 W
Lamp current (nom.)	160 mA
Starting time (nom.)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (nom.)	220-240 V
LED alternative to fluorescent lamp power	80 W
Temperature	
Ambient temperature range	-20°C to 45°C

MASTER LEDtube Mains T5

T-Case maximum (nom.)	75 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Lamp Finish	Frosted
Bulb material	Glass
Product length	1,500 mm
Bulb shape	Tube, double-ended
Approval and Application	
Energy Efficiency Class	D
Energy-saving product	Yes
Approval marks	RoHS compliance TUV CE marking KEMA Keur certificate



Energy consumption kWh/1,000 hours	36 kWh
EPREL registration number	403646
Product Data	
Full EOC	871951429050100
Order product name	MAS LEDtube 1500mm UO 36W 830 T5
Order code	29050100
SAP numerator – quantity per pack	1
Numerator – packs per outer box	10
Material no. (12 NC)	929002474802
Full product name	MASTER LEDtube 1500mm UO 36W 830 T5
EAN/UPC - Case	8719514290518
EAN/UPC - Product/Case	8719514290501

Dimensional drawing



Product	D1	D2	A1	A2	A3
MAS LEDtube 1500mm UO 36W 830 T5	15.5 mm	18.8 mm	1,449 mm	1,456.1 mm	1,463.2 mm

Photometric data




General uniform lighting - MAS LEDtube 1500mm UO 36W 830 T5

Light Distribution Diagram - MAS LEDtube 1500mm UO 36W 830 T5


MASTER LEDtube Mains T5

Photometric data




Spectral Power Distribution Colour - MAS LEDtube 1500mm UO 36W 830 T5


Lifetime




Life Expectancy Diagram - MAS LEDtube 1500mm UO 36W 830 T5



Life Expectancy Diagram




Lumen Maintenance Diagram - MAS LEDtube 1500mm UO 36W 830 T5



Lumen Maintenance Diagram - MAS LEDtube 1500mm UO 36W 830 T5

MASTER LEDtube Mains T5

Lifetime



Life Expectancy Diagram

