



Tab.32 L.S.F. - S.W.A. Cables Ref. 694*B BS6724

XLPE Insulated, LSF Bedded, Galvanised Steel Wire Armoured, LSF Black Sheathed, Class 2 Copper Conductor, Voltage Rating 600/1000V

UK Ref. CODE	PX CODE	No. Cores	Conductor		Approx.	Approx.	Drum
			Size	Constr.	O.D. MM	Weight / KM	
6942B	6942B 1.5	2	1.5	Class 2	13	300 KG	
6942B	6942B 2.5	2	2.5	Class 2	14	370 KG	
6942B	6942B 4	2	4	Class 2	15	430 KG	
6942B	6942B 6	2	6	Class 2	16.5	510 KG	
6942B	6942B 10	2	10	Class 2	19	780 KG	
6942B	6942B 16	2	16	Class 2	21	930 KG	
6943B	6943B 1.5	3	1.5	Class 2	13.5	350 KG	
6943B	6943B 2.5	3	2.5	Class 2	14.5	420 KG	
6943B	6943B 4	3	4	Class 2	16	510 KG	
6943B	6943B 6	3	6	Class 2	17	670 KG	
6943B	6943B 10	3	10	Class 2	20	940 KG	
6943B	6943B 16	3	16	Class 2	22	1,230 KG	
6944B	6944B 1.5	4	1.5	Class 2	14.5	400 KG	
6944B	6944B 2.5	4	2.5	Class 2	15.5	470 KG	
6944B	6944B 4	4	4	Class 2	17	580 KG	
6944B	6944B 6	4	6	Class 2	19.5	820 KG	
6944B	6944B 10	4	10	Class 2	21.5	1,090 KG	
6944B	6944B 16	4	16	Class 2	23.5	1,700 KG	