



collingwood

01604 495 151
collingwoodlighting.com

collingwoodled

/collingwoodlighting

collingwoodlighting

Uniform CSP

1200mm Surface Linear

Features

IK rating	IK08
IP rating	IP44 (ceiling surface mount) IP40 (suspended or wall mounted)
CSP Switchable	Yes, Wattage
UGR	<22
Sensor Option	Bolt-On PIR
Dimmable Option	Yes (DALI 2, PUSH-DIM)
LED Lifetime	70,000h L80
Emergency Option	Yes, Self-Test

Installation information

Install Connector Type	Push-fit terminal, loop-in/loop-out
Construction Material	Carbon Sheet Steel Housing, Polycarbonate Diffuser
Maximum Ambient Temperature	-20°C to +40°C
Electric Class (1, 2, 3)	1

Guarantee

5 years (product), 3 years (emerg battery), 2 years (on-site)

Features & benefits

Wattage switchable between 20W, 23W, 26W & 30W

Ultra-efficient up to 150 Llm/W

Quick and easy installation with Push-fit terminal

CSP Collingwood Switchable Product enables one luminaire to meet various lux levels within a project using a lumen output switch

Outstanding uniform lit effect

70,000 hours L80 lifetime

IP44 rated allows the product to be used in a wide range of applications

Bolt-on range of lighting controls and emergency conversion packs to aid fast availability

RG0 (Risk Exempt) Photo-biological Risk

SSuspension kit available (UNLSUS2M)

Photometrics @ 25°C

Product code	Finish	Feature I	Feature II	W	Colour	Beam	lm	llm/W	EM
UNL4SN	White RAL9016	Non-Dimmable with Wattage Output Switch	-	20W - 23W - 26W - 30W	4000K	120°	2822 3383 3984 4500	150 - 150 - 150 - 150	-
UNL4SNE	White RAL9016	Non-Dimmable with Wattage Output Switch	Emergency	20W - 23W - 26W - 30W	4000K	120°	2822 3383 3984 4500	150 - 150 - 150 - 150	325lm
UNL4SD	White RAL9016	DALI-2 Dimmable	-	30W	4000K	120°	4500	150	-
UNL4SDE	White RAL9016	DALI-2 Dimmable	Emergency	30W	4000K	120°	4500	150	325lm

Accessories

PIRBOLT	On-off PIR sensor with daylight switch	Sold Separately
PIRBOLTDIM	Dimming PIR Sensor with Lux level switch	Sold Separately
PIRBOLTDIMR	Remote control for use with PIRBOLTDIM	Sold Separately
EMBOLTMOPEN	Bolt-on emg conversion pack, Man-Test, 200lm	Sold Separately
EMBOLTMCOR	Bolt-on emg conversion pack, Man-Test, 200lm	Sold Separately
EMBOLTSOPEN	Bolt-on emg conversion pack, Self-Test, 200lm	Sold Separately
EMBOLTSCOR	Bolt-on emg conversion pack, Self-Test, 200lm	Sold Separately

Beam angle: 120°

