



FL02

20W colour switchable floodlight

Features

IK rating	IK07
IP rating	IP65
CSP Switchable	Colour switchable
Tiltable	180°
Rotation Angle	360°
UGR	UGR 14
Sensor Option	No
Dimmable Option	No
LED Lifetime	50,000h L70
CRI	80 Ra
SDCM	5 SDCM

Installation information

Install Connector Type	Flying lead
Inrush Current	11A 4745
Construction Material	Black painted cast aluminium
Weight	580g
Maximum Ambient Temperature	-40°C to 40°C
Electric Class (1, 2, 3)	1

Wiring information

Cable / Flying Lead	1m H05RN-F rubberised cable 3x1.0mm² Ø7mm
Type of Wiring Required	Parallel

Accessories

N/A	No accessories required
-----	-------------------------



collingwood

01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

5 years for standard & 3 years for PIR

Features & benefits

High efficacy of up to 120lm/W

First fix bracket for quick & easy installation

Ideal for coastal areas

Colour switchable between 3 colour temperatures

IP65 rated, meaning it provides optimum protection against the impacts of rainwater and general adverse weather conditions

A unique 360° rotation for total flexibility, and a 180° tilt

Supplied with 1m cable



Wide 120° beam angle, reducing the number of fittings per area required

Performs in even more extreme conditions from -40°C to +40°C

Light source energy efficiency:



Beam angles: C0/C180 C90/C270



Photometrics @ 25°C

	Finish	Feature I	W	Colour	Beam	lm	lm/W	lx @ 1m
FL02BXCS	Black	Non PIR sensor	20W	3000K	120°	2200	110	832
FL02BXCS	Black	Non PIR sensor	20W	4000K	120°	2400	120	1040
FL02BXCS	Black	Non PIR sensor	20W	6500K	120°	2400	120	999
FL02BPCS	Black	PIR sensor	20W	3000K	120°	2200	110	832
FL02BPCS	Black	PIR sensor	20W	4000K	120°	2400	120	1040
FL02BPCS	Black	PIR sensor	20W	6500K	120°	2400	120	999
FL02WXCS	White RAL9016	Non PIR sensor	20W	3000K	120°	2200	110	832
FL02WXCS	White RAL9016	Non PIR sensor	20W	4000K	120°	2400	120	1040
FL02WXCS	White RAL9016	Non PIR sensor	20W	6500K	120°	2400	120	999
FL02WPCS	White RAL9016	PIR sensor	20W	3000K	120°	2200	110	832
FL02WPCS	White RAL9016	PIR sensor	20W	4000K	120°	2400	120	1040
FL02WPCS	White RAL9016	PIR sensor	20W	6500K	120°	2400	120	999
FL02AXCS	Anthracite grey RAL7016	Non PIR sensor	20W	3000K	120°	2200	110	832
FL02AXCS	Anthracite grey RAL7016	Non PIR sensor	20W	4000K	120°	2400	120	1040
FL02AXCS	Anthracite grey RAL7016	Non PIR sensor	20W	6500K	120°	2400	120	999
FL02APCS	Anthracite grey RAL7016	PIR sensor	20W	3000K	120°	2200	110	832
FL02APCS	Anthracite grey RAL7016	PIR sensor	20W	4000K	120°	2400	120	1040
FL02APCS	Anthracite grey RAL7016	PIR sensor	20W	6500K	120°	2400	120	999



collingwood

01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

FL02

With a wide 120° beam angle and a unique 360° rotation, this 20W flicker-free floodlight is the ideal solution for outdoor use, lighting large areas, courtyards and entrances or for uplighting trees and buildings. With a market leading efficacy and contemporary black cast aluminium body, this colour switchable light is a versatile solution for your space.

Choose the PIR sensor option for added security and reduction of energy bills in highly trafficked areas.