



FL05

50W colour switchable floodlight

Features

IK rating	IK07
IP rating	IP65
CSP Switchable	Colour switchable
Tiltable	180°
Rotation Angle	360°
UGR	UGR 14
Sensor Option	No
Dimmable Option	No
LED Lifetime	50,000h L70
CRI	80 Ra
SDCM	4 SDCM

Installation information

Install Connector Type	Flying lead
Inrush Current	28A 13s
Construction Material	Black painted cast aluminium
Weight	1220g
Maximum Ambient Temperature	-40°C to 40°C
Electric Class (1, 2, 3)	1

Wiring information

Cable / Flying Lead	1m H05RN-F rubberised cable 3x1.0mm² Ø7mm
Type of Wiring Required	Parallel

Accessories

N/A	No accessories required
-----	-------------------------



01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

5 years for standard & 3 years for PIR



Features & benefits

- High efficacy of up to 112lm/W
- First fix bracket for quick & easy installation
- Ideal for coastal areas
- Colour switchable between 3 colour temperatures
- IP65 rated, meaning it provides optimum protection against the impacts of rainwater and general adverse weather conditions
- A unique 360° rotation for total flexibility, and a 180° tilt
- Supplied with 1m cable
- Wide 120° beam angle, reducing the number of fittings per area required
- Performs in even more extreme conditions from -40°C to +40°C

Light source
energy efficiency:



Beam angles: **C0/C180** **C90/C270**



Photometrics @ 25°C

	Finish	Feature I	W	Colour	Beam	lm	lm/W	lx @ 1m
FL05BXCS	Black	Non PIR sensor	50W	3000K	120°	5000	100	2230
FL05BXCS	Black	Non PIR sensor	50W	4000K	120°	5600	112	2449
FL05BXCS	Black	Non PIR sensor	50W	6500K	120°	5100	102	2230
FL05BPCS	Black	PIR sensor	50W	3000K	120°	5000	100	2230
FL05BPCS	Black	PIR sensor	50W	4000K	120°	5600	112	2449
FL05BPCS	Black	PIR sensor	50W	6500K	120°	5100	102	2230
FL05WXCS	White RAL9016	Non PIR sensor	50W	3000K	120°	5000	100	2230
FL05WXCS	White RAL9016	Non PIR sensor	50W	4000K	120°	5600	112	2449
FL05WXCS	White RAL9016	Non PIR sensor	50W	6500K	120°	5100	102	2230
FL05WPCS	White RAL9016	PIR sensor	50W	3000K	120°	5000	100	2230
FL05WPCS	White RAL9016	PIR sensor	50W	4000K	120°	5600	112	2449
FL05WPCS	White RAL9016	PIR sensor	50W	6500K	120°	5100	102	2230
FL05AXCS	Anthracite grey RAL7016	Non PIR sensor	50W	3000K	120°	5000	100	2230
FL05AXCS	Anthracite grey RAL7016	Non PIR sensor	50W	4000K	120°	5600	112	2449
FL05AXCS	Anthracite grey RAL7016	Non PIR sensor	50W	6500K	120°	5100	102	2230
FL05APCS	Anthracite grey RAL7016	PIR sensor	50W	3000K	120°	5000	100	2230
FL05APCS	Anthracite grey RAL7016	PIR sensor	50W	4000K	120°	5600	112	2449
FL05APCS	Anthracite grey RAL7016	PIR sensor	50W	6500K	120°	5100	102	2230



collingwood

01604 495 151
collingwoodlighting.com

 collingwoodled

 /collingwoodlighting

 collingwoodlighting

FL05

With a wide 120° beam angle and a unique 360° rotation, this 10W flicker-free floodlight is the ideal solution for outdoor use, lighting large areas, courtyards and entrances or for uplighting trees and buildings. With a market leading efficacy and contemporary black cast aluminium body, this colour switchable light is a versatile solution for your space.