

3x1.0+1.0 SOL CU PVC PVC 0.5kV 6243Y GRY

6243Y. PVC Flat Wiring Cable with Bare CPC. BS 6004. 300/500 V



Prysmian 6243Y is a flat PVC insulated and sheathed low voltage wiring cable typically used for small power and lighting applications. Three cores with bare CPC.

KEY APPLICATIONS

Suitable for fixed installation in industrial, commercial and domestic premises, installation in walls, on boards, in conduit, trunking or embedded in plaster for small power and lighting applications.

FEATURES AND BENEFITS

- Ideal for ring and radial circuits
- Ideal for lighting and switching circuits
- Easy to strip
- Manufactured under ISO 9001 Quality management systems

STANDARDS



BS 6004

BS EN 60332-1-2

Construction Standard

Flame Propagation - Single Cable

CONSTRUCTION

Conductor material

Copper

Conductor surface

Bare

Core insulation material

Polyvinyl chloride (PVC)

Material outer sheath

Polyvinyl chloride (PVC)

Cable shape

Flat

APPLICATIONS PROPERTIES

Nominal voltage U0 [V]	300
Nominal voltage U [V]	500
Flame retardant	In accordance with BS EN 60332-1-2
Max. conductor temperature [°C]	70
Min. Operation temperature [°C]	-15
Min. Installation temperature [°C]	0
Max. Installation temperature [°C]	60
Bending radius (rule)	4D (Minor axis)

COLOURS

Insulation: Brown, Black, Grey

Sheath: Grey

CURRENT RATINGS

Refer to table 4D5 of BS 7671 Requirements for Electrical Installations. IET Wiring Regulations

TECHNICAL DATA

Number of cores	3
Nominal cross section conductor [mm²]	1
Conductor category	Class 1 = solid
Nominal cross section of protective conductor [mm²]	1
Cable height approx. [mm]	4.5
Cable width approx. [mm]	10.7
Cable weight [kg/km]	78
Conductor resistance at 20° C [Ohm/km]	18.1

*The embodied carbon figure is taken from a single product in the range, for more information on how we calculate our embodied carbon figure visit here: <https://uk.prysmiangroup.com/embodied-carbon>