Eaton EMDH132

Catalog Number: EMDH132

Eaton Moeller series xPole UK - EM.H MCB. EM, 1-pole, trip type: D, rated current In: 32 A, rated switching capacity IEC/EN 60947-2: 15 kA, rated switching capacity IEC/EN 60898-1: 10 kA

General specifications



Eaton Moeller series xPole UK - EM.H EMDH132

MCB

Model Code

EMDH132

EAN Product Length/Depth

5019586121820 85 mm

Product Height Product Width

73 mm 17.5 mm

Product Weight Compliances
0.121 kg RoHS conform





Product specifications

Resources

Number of poles (protected) 1
Rated short-circuit breaking capacity (EN 60898) at 230 V 10 kA
Release characteristic D
Current limiting class 3
Rated short-circuit breaking capacity (EN 60898) at 400 V 10 kA
Amperage Rating 32 A
Frequency rating - max 60 Hz
Width in number of modular spacings 1
Rated short-circuit breaking capacity (IEC 60947-2) at 400 V 15 kA
Connectable conductor cross section (solid-core) - max 25 mm²
Number of poles (total) 1
Degree of protection IP20
Overvoltage category III
Rated short-circuit breaking capacity (IEC 60947-2) at 230 V 15 kA
Ambient operating temperature - max 75 °C
Pollution degree 2
Connectable conductor cross section (multi-wired) - min 1 mm ²
Rated impulse withstand voltage (Uimp)

Voltage type

Rated insulation voltage (Ui)

AC

440 V



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2023 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia