

Eaton 152535

Catalog Number: 152535

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 1p, 50A, B



General specifications

Product Name	Catalog Number
Eaton Moeller series NZM molded case circuit breaker thermo-magnetic	152535
	Model Code
	NZMB1-1-AF50
EAN	Product Length/Depth
4015081492817	88 mm
Product Height	Product Width
145 mm	30 mm
Product Weight	Compliances
0.439 kg	RoHS conform
Certifications	
IEC	
IEC/EN 60947	

Technical data - electrical

Voltage rating

230 V - 230 V

Rated impulse withstand voltage (Uimp) at auxiliary contacts

6000 V

Rated impulse withstand voltage (Uimp) at main contacts

6000 V

Amperage Rating

50 A

Instantaneous current setting (Ii) - min

600 A

Instantaneous current setting (Ii) - max

600 A

Overload current setting (Ir) - min

50 A

Overload current setting (Ir) - max

50 A

Short delay current setting (I_{sd}) - min

0 A

Short delay current setting (I_{sd}) - max

0 A

Short-circuit release non-delayed setting - min

600 A

Short-circuit release non-delayed setting - max

600 A

Rated short-circuit breaking capacity I_{cs} (IEC/EN 60947) at 230 V, 50/60 Hz

25 kA

Rated short-circuit breaking capacity I_{cs} (IEC/EN 60947) at 400/415 V, 50/60 Hz

25 kA

Rated short-circuit breaking capacity I_{cs} (IEC/EN 60947) at 440 V, 50/60 Hz

18.5 kA

Rated short-circuit making capacity I_{cm} at 240 V, 50/60 Hz

55 kA

Rated short-circuit making capacity I_{cm} at 400/415 V, 50/60 Hz

53 kA

Technical data - communication

Rated impulse withstand voltage (Uimp) at auxiliary contacts

6000 V

Rated impulse withstand voltage (Uimp) at main contacts

6000 V

Amperage Rating

50 A

Instantaneous current setting (Ii) - min

600 A

Instantaneous current setting (Ii) - max

600 A

Overload current setting (Ir) - min

50 A

Overload current setting (Ir) - max

50 A

Short delay current setting (I_{sd}) - min

0 A

Short delay current setting (I_{sd}) - max

0 A

Short-circuit release non-delayed setting - min

600 A

Short-circuit release non-delayed setting - max

600 A

Rated short-circuit breaking capacity I_{cs} (IEC/EN 60947) at 230 V, 50/60 Hz

25 kA

Rated short-circuit breaking capacity I_{cs} (IEC/EN 60947) at 400/415 V, 50/60 Hz

25 kA

Rated short-circuit breaking capacity I_{cs} (IEC/EN 60947) at 440 V, 50/60 Hz

18.5 kA

Rated short-circuit making capacity I_{cm} at 240 V, 50/60 Hz

55 kA

Rated short-circuit making capacity I_{cm} at 400/415 V, 50/60 Hz

53 kA

Rated short-circuit making capacity I_{cm} at 440 V, 50/60 Hz

53 kA

Rated short-circuit making capacity I_{cm} at 440 V, 50/60 Hz

53 kA

Short-circuit total breaktime

< 10 ms

Electrical connection type of main circuit

Frame clamp

Isolation

300 V AC (between the auxiliary contacts)

500 V AC (between auxiliary contacts and main contacts)

Number of operations per hour - max

120

Handle type

Rocker lever

Utilization category

A (IEC/EN 60947-2)

Overvoltage category

III

Pollution degree

3

Direction of incoming supply

As required

Short-circuit total breaktime

< 10 ms

Electrical connection type of main circuit

Frame clamp

Isolation

300 V AC (between the auxiliary contacts)

500 V AC (between auxiliary contacts and main contacts)

Number of operations per hour - max

120

Handle type

Rocker lever

Utilization category

A (IEC/EN 60947-2)

Overvoltage category

III

Pollution degree

3

Direction of incoming supply

As required

Technical data - mechanical

Mounting Method

Fixed

Built-in device fixed built-in technique

Degree of protection

IP20

IP20 (basic degree of protection, in the operating controls area)

Degree of protection (IP), front side

IP66 (with door coupling rotary handle)

IP40 (with insulating surround)

Degree of protection (terminations)

IP10 (tunnel terminal)

IP00 (terminations, phase isolator and strip terminal)

Protection against direct contact

Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part

110

Shock resistance

20 g (half-sinusoidal shock 20 ms)

Number of auxiliary contacts (change-over contacts)

0

Number of auxiliary contacts (normally closed contacts)

0

Number of auxiliary contacts (normally open contacts)

0

Position of connection for main current circuit

Front side

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

Lifespan, mechanical

20000 operations

Resources

Brochures

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)

[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

Catalogues

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

Characteristic curve

[eaton-circuit-breaker-characteristic-power-defense-mccb-characteristic-curve-032.eps](#)

[eaton-circuit-breaker-characteristic-power-defense-mccb-characteristic-curve-038.eps](#)

eCAD model

[DA-CE-ETN.NZMB1-1-AF50](#)

Installation videos

[Introduction of the new digital circuit breaker NZM](#)

[The new digital NZM Range](#)

mCAD model

[DA-CD-nzm1_1p](#)

[DA-CS-nzm1_1p](#)

Technical data sheets

[eaton-nzm-technical-information-sheet](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](#)