

Eaton CEO80

Catalog Number: CEO80

Fuse-link, LV, 80 A, AC 500 V, BS88/A4, 25 x 110 mm, gL/gG, BS



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage	CEO80
British standard fuse	EAN
	5027590496322
UPC	Product Length/Depth
051712839495	109.5 mm
Product Height	Product Width
24.5 mm	21 mm
Product Weight	Warranty
77.6 g	Not Applicable
Compliances	Certifications
CE Marked	IEC 60269-2
RoHS Compliant	BS88

Product specifications

Interrupt rating

80 kAIC

Center-to-center distance of connections

94 mm

Insulated metal gripping lugs (IMGL)

No

Current type

AC

Suitable for

RS100 Red spot fuse holder

Amperage Rating

80 A

Fuse type

CEO

Fuse system (according to IEC 60269)

Fuse system E

Fitted with:

Offset bolted tags

Rated switching capacity

80 kA

Fuse size

BS88/A4

Voltage rating

500 V

Fuse indicator

None

Construction

BS88/A4

Construction size

A4

Rated voltage AC

500 V

Color

None

Connection

Resources

Compliance information

[UKCA AAO,BAO,CEO,NITD,NIT,GTIS,CEO100M,GTIS63M](#)

[CE AAO,BAO,CEO,NITD,NIT,GTIS,CEO100M,GTIS63M](#)

Installation videos

[Video BS88 industrial fuse links](#)

Technical data sheets

[4115 CEO fuses](#)

Technical service bulletins

[Datasheet - CEO80](#)

94 mm fixing centre

Mounting dimension

M8

Utilization category

gL/gG (cable protection/equipment protection)

Watt losses

7.2 W

Type

Fuse

Fuse shape

Offset bolted tags

Breaking capacity

80 kA

Class

Class gG/gL

Application

general industrial applications

Voltage type

AC



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia