

# Eaton DEO160

Catalog Number: DEO160

Fuse-link, LV, 160 A, AC 415 V, BS88, 31 x 110 mm, gL/gG, BS



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series low voltage British standard fuse	DEO160
	<b>EAN</b>
	5027590497787
<b>UPC</b>	<b>Product Length/Depth</b>
051712839631	110 mm
<b>Product Height</b>	<b>Product Width</b>
29.5 mm	31 mm
<b>Product Weight</b>	<b>Warranty</b>
141.4 g	Not Applicable
<b>Compliances</b>	<b>Certifications</b>
CE Marked	IEC 60269-2
RoHS Compliant	BS88

## Electrical rating

### Amperage Rating

160 A

### Breaking capacity

80 kA

### Interrupt rating

80 kAIC

### Rated switching capacity

80 kA

### Voltage rating

415 V

### Voltage type

AC

## Physical details

### Color

None

### Fuse type

DEO

## General information

### Class

Class gG/gL

### Connection

94 mm fixing centre

### Construction size

Other

### Fitted with:

Offset bolted tags

### Fuse indicator

None

### Fuse shape

Offset bolted tags

### Insulated metal gripping lugs (IMGL)

No

### Utilization category

gL/gG (cable protection/equipment protection)

## Resources

### Compliance information

[UKCA DEO OSD motor start](#)

[CE DEO OSD motor start](#)

### Installation videos

[Video BS88 industrial fuse links](#)

### Technical data sheets

[4117 DEO fuses](#)

### Technical service bulletins

[Datasheet - DEO160](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2023 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)