

Eaton NSD20M25

Catalog Number: NSD20M25

Fuse-link, low voltage, 20A, AC 415 V, BS88/F2, 18 x 59 mm, gM, BS, 20M25



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage	NSD20M25
British standard fuse	EAN
	5027590504836
UPC	Product Length/Depth
051712840293	58.5 mm
Product Height	Product Width
13.8 mm	13.8 mm
Product Weight	Warranty
16.2 g	Not Applicable
Compliances	Certifications
CE Marked	IEC 60269-2
RoHS Compliant	BS88

Electrical rating

Amperage Rating

20 A

Breaking capacity

80 kA

Interrupt rating

80 kAIC

Rated switching capacity

80 kA

Voltage rating

415 V

Voltage type

AC

Physical details

Color

None

Fuse type

NSD

General information

Class

Class gM

Connection

Blade end

Construction size

F2

Fitted with:

Offset bladed tags

Fuse indicator

None

Fuse shape

Offset bladed tags

Fuse size

BS88/F1

Insulated metal gripping lugs (IMGL)

No

Utilization category

gM (motor protection)

Resources

Compliance information

UKCA NSDx, NSD20Mx, NSD32Mx

CE NSDx, NSD20Mx, NSD32Mx

Installation videos

Video BS88 industrial fuse links

Technical data sheets

4100 NSD fuses

Technical service bulletins



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All rights reserved.

Eaton is a registered trademark.
All other trademarks are property of their respective owners.



Eaton.com/socialmedia