

Eaton STD6

Catalog Number: STD6

Fuse-link, LV, 6 A, AC 240 V, BS88, 12 x 47 mm, gL/gG, BS



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage	STD6
British standard fuse	UPC
	051712844642
EAN	Product Length/Depth
5027590512657	47 mm
Product Height	Product Width
12 mm	13 mm
Product Weight	Warranty
11.05 g	Not Applicable
Compliances	Certifications
CE Marked	BS88
RoHS Compliant	IEC 60269

Especificaciones del producto

Recursos

Interrupt rating

33 kAIC

Center-to-center distance of connections

35 mm

Insulated metal gripping lugs (IMGL)

No

Current type

AC

Amperage Rating

6 A

Fuse type

STD

Fuse system (according to IEC 60269)

Other

Fitted with:

Offset bolted tags

Rated switching capacity

33 kA

Voltage rating

240 V

Fuse indicator

None

Construction

BS88

Construction size

Other

Rated voltage AC

240 V

Color

None

Connection

Bolt-on

Mounting dimension

Other

Utilization category

gL/gG (cable protection/equipment protection)

Watt losses

1.6 W

Type

Fuse

Fuse shape

Offset slotted bolted tags

Breaking capacity

33 kA

Class

Class gG/gL

Application

street lighting cut-outs

Voltage type

AC



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. Todos los
derechos reservados.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia