

# Eaton NITD32M40

Catalog Number: NITD32M40

Fuse-link, LV, 32 A, AC 415 V, BS88/A1, 18 x 55 mm, gM, BS, 32M40



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series low voltage British standard fuse	NITD32M40
	<b>EAN</b> 5027590504126
<b>UPC</b> 051712844383	<b>Product Length/Depth</b> 57 mm
<b>Product Height</b> 18 mm	<b>Product Width</b> 18 mm
<b>Product Weight</b> 27.05 g	<b>Warranty</b> Not Applicable
<b>Compliances</b> RoHS Compliant CE Marked	<b>Certifications</b> BS88 IEC 60269 EAC

## Electrical rating

### Amperage Rating

32 A

### Breaking capacity

80 kA

### Interrupt rating

80 kAIC

### Rated switching capacity

80 kA

### Voltage rating

415 V

### Voltage type

AC

## Physical details

### Color

None

### Fuse type

NITD

## Resources

### Compliance information

[UKCA AAO BAO NIT NITD motor start](#)

[CE AAO BAO NIT NITD motor start](#)

### Installation videos

[Video BS88 industrial fuse links](#)

### Technical data sheets

[4106 NITD fuses](#)

### Technical service bulletins

[Datasheet - NITD32M40](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2023 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)