

Eaton C10G16

Catalog Number: C10G16

Eaton Bussmann series low voltage 10 x 38 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 16 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CHM Modular fuse holder



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C10G16
	Model Code
	CYLINDRICAL FUSE 10 x 38 16A GG 500V AC
EAN	UPC
5027590493437	051712754286
Product Length/Depth	Product Height
38 mm	10 mm
Product Width	Product Weight
10 mm	8.2 g
Warranty	Compliances
1 year limited	CE Marked
	GoST-R
	RoHS Compliant
Certifications	
IEC 60269	

Product specifications

Fuse indicator

Other

Construction size

10 mm x 38 mm

Rated voltage AC

500 V

Connection

Ferrule end x ferrule end

Quantity

10

Current type

AC

Suitable for

CHM Modular fuse holder

Material

Ceramic

Mounting method

Holder

Release characteristic

Other

Amperage Rating

16 A

Frequency rating - max

62 Hz

Utilization category

gG (cable protection/equipment protection)

Watt losses

1.6 W

Fuse type

C10G

Type

fuse

Fuse shape

Cylindrical

Resources

Compliance information

[UKCA C08G, C08M, etc cylindrical fuselinks](#)

[CE C08G, C08M, etc cylindrical fuselinks](#)

Installation videos

[Video Cylindrical fuse link portfolio](#)

Technical data sheets

[720115 Cylindrical fuses](#)

Technical service bulletins

[Datasheet - C10G16](#)

Breaking capacity

120 kA

Fuse size

10 x 38 mm

Frequency rating - min

45 Hz

Class

Class C gL/gG

Voltage rating

500 V

Application

for industrial applications

for general purpose use

Voltage type

AC



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia