

Eaton FXROLPWR

Catalog Number: FXROLPWR

Eaton Conventional sounder VAD, Conventional, Alarms and Beacons, Sounder VAD, EN54 Systems, Wall Mounted, Red Plastic, Red Flash, RoLP

General specifications



Product Name	Catalog Number
Eaton Conventional sounder VAD	FXROLPWR
EAN	Product Length/Depth
5018987126717	95 mm
Product Height	Product Width
135 mm	95 mm
Product Weight	Compliances
0.2 kg	Contact Manufacturer

Product specifications

EN Certified Tones

6

Product branding

Eaton Cooper

Operating temperature - min

-25 °C

Type of optical signal

Flash light

Suitable for

Wall Mounting

Nominal voltage - min

18 V

Mounting Method

Surface mounting

Humidity (Non Condensing) - Max

95 %

Coverage volume

2.4 - 7.5 m3

System typology

Conventional (Non-addressable)

EN Certification Standards

EN54 Pt3 (Fire Alarm Sounders)

EN54 Pt23 (Visual Alarms)

Frequency sound signal - min

0.5 Kilo Hertz

Operating temperature - max

70 °C

Lens color

Clear

Alarm current - max

37 mA

Humidity (Non Condensing) - Min

0 %

Type of acoustic signal

Programmable

Resources

Technical data sheets

[eaton-fire-conventional-symphoni-lx-sounder-beacon-fxsyg1wr-datasheet-0619](#)

Degree of protection

IP65

Light color

Red

Cable entry

Rear

Voice tones

No

Nominal voltage - max

24 V

Electricity consumption

0.037 A

Construction material

ABS

Sound output

102 dB

Type of current

DC

Lamp type

LED

System wiring

2.5 mm

Tones

32

Frequency sound signal - max

1.2 Kilo Hertz

Compliance and standards

Accordance With EN 54-23

Type of acoustic signal device

Sound generator

Power

0.888 W

Color housing

Red



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)