



Features

TECHNICAL INFORMATION

Minimum operating temperature	-40 °C
Maximum operating temperature	130 °C
Self-extinguishing fire class according to UL 94	V0

LOGISTIC

Customs code	39269097
--------------	----------

MATERIAL COMPOSITION AND TREATMENTS

Material	Polycarbonate
Silicone-free	Yes
Halogen free	Yes

CLASSIFICATION AND DATA ORDERING

ETIM Class 7	Labelling for terminal block [EC000761]
Manufactured in	Italy

MG-CPM-01

tipo	Color	Sheet elements	Number of lines	Number of columns	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Horizontal pitch between the sheet elements [mm]	Gross weight [g]	Storage temperature [°c]	Relative humidity of storage	Software code	Ribbon	Printable with	Plates
41091N	White	48			5	15	15	5	5,1	0,293			16			991011
41094	White	56	4	14	5	7	7	5	5,1	0,169	10 ÷ 25	45 ÷ 55	13	MG2-ETR	MG3; MG4	MG2-MTB
41090N	White	56	4	14	5	10	10	5	5,1	0,228	10 ÷ 25	45 ÷ 55	14	MG2-ETR	MG3; MG4	MG2-QTB
41096	White	32			8	10	10	8	8	0,443			18	MG2-ETR	MG3; MG4	991011
41092	White	80	4	20	3	10	10	3	3,5	0,154	10 ÷ 25	45 ÷ 55	15	MG2-ETR	MG3; MG4	MG2-QTB
41095	White	48	4	12	6	10	10	6	6	0,234	10 ÷ 25	45 ÷ 55	17	MG2-ETR	MG3; MG4	MG2-QTB
41040N	Yellow	56			5	10	10	5	5,1	0,228			14	MG2-ETR	MG3; MG4	991011
41044	Yellow	56			5	7	7	5	5,6	0,168			13	MG2-ETR	MG3; MG4	991008
41046	Yellow	32			8	10	10	8	8	0,425			18	MG2-ETR	MG3; MG4	991011
41041N	Yellow	48			5	15	15	5	5,1	0,291			16	MG2-ETR	MG3; MG4	991011
41045	Yellow	48			6	10	10	6	6	0,233			17	MG2-ETR	MG3; MG4	991011