

TAGES FOR CABLES AND COMPONENTS, PRE-CUT, RIGID PVC



Features

TECHNICAL INFORMATION

Minimum operating temperature	-30 °C
Maximum operating temperature	60 °C
Self-extinguishing fire class according to UL 94	V0

WEIGHT AND DIMENSIONS

Width	9 mm
-------	------

CLASSIFICATION AND DATA ORDERING

ETIM Class 7	Labelling material [EC001288]
Manufactured in	Italy

MATERIAL COMPOSITION AND TREATMENTS

Material	Rigid PVC
Silicone-free	Yes

LOGISTIC

Customs code	39204910
--------------	----------

MG-TAPW

tipo	Color	Sheet elements	Number of lines	Number of columns	Halogen free	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Storage temperature [°C]	Relative humidity of storage	Software code	Ribbon	Printable with	Plates
49090N	White	55	5	11	No	20	9	20	0,225	10 ÷ 25	45 ÷ 55	362	MG2- ETR	MG3; MG4	MG2- PLT
49040N	Yellow	55	5	11	No	20	9	20	0,222	10 ÷ 25	45 ÷ 55	362	MG2- ETR	MG3; MG4	MG2- PLT
49042N	Yellow	88	8	11	No	12	9	12	0,142	10 ÷ 25	45 ÷ 55	360	MG2- ETR	MG3; MG4	MG2- PLT
49043N	Yellow	77	7	11	No	15	9	15	0,163	10 ÷ 25	45 ÷ 55	361	MG2- ETR	MG3; MG4	MG2- PLT
49044	Yellow	20	2	10	No	50	9	50	0,615	10 ÷ 25	45 ÷ 55	376	MG2- ETR	MG3; MG4	MG2- PLT
49045N	Yellow	11				70			1,025			378			
49091N	White	33	3	11	No	35	9	35	0,368	10 ÷ 25	45 ÷ 55	364	MG2- ETR	MG3; MG4	MG2- PLT
49093N	White	77	7	11	No	15	9	15	0,165	10 ÷ 25	45 ÷ 55	361	MG2- ETR	MG3; MG4	MG2- PLT
49094	White	20	2	10	No	50	9	50	0,613	10 ÷ 25	45 ÷ 55	376	MG2- ETR	MG3; MG4	MG2- PLT
49092N	White	88	8	11	No	12	9	12	0,145	10 ÷ 25	45 ÷ 55	360	MG2- ETR	MG3; MG4	MG2- PLT
49041N	Yellow	33	3	11	No	35	9	35	0,367	10 ÷ 25	45 ÷ 55	364	MG2- ETR	MG3; MG4	MG2- PLT
49095N	White	11	1	11	No	70	9	70	1,156	10 ÷ 25	45 ÷ 55	378	MG2- ETR	MG3; MG4	MG2- PLT
49046	Yellow	30	3	10	No	29	9	30	0,422	10 ÷ 25	45 ÷ 55	363	MG2- ETR	MG3; MG4	MG2- PLT
49066	Blue	30	3	10	No	29	9	30	0,407	10 ÷ 25	45 ÷ 55	363	MG2- ETR	MG3; MG4	MG2- PLT
49053N	Green	77	7	11	No	15	9	15		10 ÷ 25	45 ÷ 55	361	MG2- ETR	MG3; MG4	MG2- PLT
49055N	Green	11				70						378			
49096	White	30	3	10	No	29	9	30	0,420	10 ÷ 25	45 ÷ 55	363	MG2- ETR	MG3; MG4	MG2- PLT