



Features

TECHNICAL INFORMATION

Minimum operating temperature	-40 °C
Maximum operating temperature	130 °C
Self-extinguishing fire class according to UL 94	V0

WEIGHT AND DIMENSIONS

Width	4 mm
Height of the printable area	4 mm

CLASSIFICATION AND DATA ORDERING

ETIM Class 7	Labelling material [EC001288]
Manufactured in	Italy

MATERIAL COMPOSITION AND TREATMENTS

Material	Polycarbonate
Silicone-free	Yes
Halogen free	Yes

LOGISTIC

Customs code	39269097
--------------	----------

COMPATIBILITY

Ribbon	MG2-ETR
Printable with	MG3; MG4

MG-TDM-01

Range of cable housing diameter
1.6 ÷ 3.25 mm

Range of cable cross section
0.5 ÷ 1.5 mm²

tipo	Color	Sheet elements	Number of lines	Number of columns	L [mm]	Base of the printable area [mm]	Gross weight [g]	Storage temperature [°c]	Relative humidity of storage	Software code	Plates
40190	White	66	6	11	12	12	0,273	10 ÷ 25	45 ÷ 55	121	991007
40191	White	40	4	10	16	16	0,335			123	991010
40192	White	40	4	10	12	12	0,335	10 ÷ 25	45 ÷ 55	119	MG2-PTM
40142	Yellow	40	4	10	12	12	0,336			119	991010
40140	Yellow	66	6	11	12	12	0,276	10 ÷ 25	45 ÷ 55	121	MG2-PTD
40141	Yellow	40	4	10	16	16	0,338			123	991010

MG-TDM-02

Range of cable housing diameter
2 ÷ 4.4 mm

Range of cable cross section
1 ÷ 6 mm²

tipo	Color	Sheet elements	Number of lines	Number of columns	L [mm]	Base of the printable area [mm]	Gross weight [g]	Storage temperature [°c]	Relative humidity of storage	Software code	Plates
40290	White	66	6	11	12	12	0,301	10 ÷ 25	45 ÷ 55	122	MG2-PTD
40291	White	40	4	10	16	16	0,363	10 ÷ 25	45 ÷ 55	124	MG2-PTM
40292	White	40	4	10	12	12	0,366			120	991010
40242	Yellow	40	4	10	12	12	0,369			120	991010
40240	Yellow	66	6	11	12	12	0,314			122	991007
40241	Yellow	40	4	10	16	16	0,375			124	991010