# 9001KR1U 30MM PUSH BUTTON FULL GUARD





Main	
Range of product	Harmony 9001K
Product or component type	Head for push-button
Device short name	9001K
Operator profile	Flush, unmarked
Operator additional	Metal guard

Comp	lemen <sup>-</sup>	tarv
- C C P		· ,

Mounting diameter	30 mm
Shape of signaling unit head	Round
Type of operator	Spring return
Net weight	0.087 kg
Bezel material	Metal
Cap/operator or lens colour	7 colours choice
Operator profile	Flush
Type of operator	Spring return
Contacts type and composition	Without contact block

information

## **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	9.500 cm	
Package 1 Width	5.500 cm	
Package 1 Length	5.000 cm	
Package 1 Weight	102.000 g	
Unit Type of Package 2	S01	
Number of Units in Package 2	24	
Package 2 Height	15.000 cm	
Package 2 Width	15.000 cm	
Package 2 Length	40.000 cm	
Package 2 Weight	2.622 kg	

# Offer Sustainability

Sustainable offer status	Green Premium product		
REACh Regulation	☑ REACh Declaration		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS  Declaration		
Mercury free	Yes		
China RoHS Regulation	China RoHS Declaration		
RoHS exemption information	₽¥Yes		
Environmental Disclosure	Product Environmental Profile		

Circularity Profile	No need of specific recycling operations	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Contractual warranty		


18 months


Warranty

# Product data sheet Dimensions Drawings

# 9001KR1U


# **Dimensions**





# **Contact Block Mounting Position**


#### Top and Rear views



- (1) It is possible to mount up to 3 levels of contacts blocks (maximum of 6 contacts blocks)
- (2) Operator
- (3) Locating notch
- (4) Side 1
- (5) Side 2

## Panel Cut-Out

#### Clearance



Legend plate	a min.		b min.	
	mm	in.	mm	in.
9001KN2••	57.2	2.25	44.5	1.75
9001KN3••	57.2	2.25	50.8	2.00

#### Individual Cut-outs Details

2 alternatives

mm in.

