

PRODUCT-DETAILS

KSF225DP

KSF225DP Fireman switch



General Information

Extended Product Type	KSF225DP
Product ID	2CMA142435R1000
EAN	7392696424356
Catalog Description	KSF225DP Fireman switch

Long Description

Fireman switch, 2-p. 400V AC22 25A, Aluminium enclosure, Black Side-operated handle. Interlocked cover. The enclosure of the ABB's side controlled enclosed switches are made of rigid silumin. The paint is UV protected, and enclosure is protected against low pressure water jets (IP65), and hence built for outdoor and indoor use. The cable entries are threaded and have cable entries for 2 parallell cables, both from top and bottom. Membrane grommets are included (IP54). The handle is padlockable and made for one padlock. The cover is interlocked. The switch is made for 4 wire system, and have a fixed neutral terminal and PE terminal. The terminals are easily accessible for easy installation.

Circular Value

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC340076D0201
RoHS Information	1SCC340075D0201
Toxic Substances Control Act - TSCA	1SCC340095D0201

Ordering

Minimum Order Quantity	1 piece
------------------------	---------

Customs Tariff Number	85363030
Country of Origin	Bulgaria (BG)

Popular Downloads

Data Sheet, Technical Information	1SCC340015C0201
Instructions and Manuals	9AKK108467A6812
Mechanical Drawings	LBA1R131160DM25.stp

Dimensions

Product Net Width	111 mm
Product Net Height	130 mm
Product Net Depth / Length	60 mm
Product Net Weight	0.57 kg

Technical

Rated Operational Current AC-22A (I_g)	(230 V) Single Phase 25 A
Rated Operational Current AC-23A (I_g)	(230 V) Single Phase 25 A
Rated Operational Power AC-23A (P_g)	(230 V) Single Phase 3.7 kW
Conventional Free-air Thermal Current (I_{th})	25 A
Conventional Thermal Current (I_{the})	Fully Enclosed 25 A
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 690 V
Rated Operational Voltage	Main Circuit 690 V
Handle Color	Black
Handle Type	Side-operated handle
Standards	IEC 60947-1, -3
Number of Poles	2
Neutral Type	No neutral terminal
Connecting Capacity Main Circuit	Screw Clamp 0.75 ... 10 mm ² Screw Clamp / PE Terminal 1pc, 0.75 ... 10 mm ²
Cable Cross-Section	0.75 ... 10 mm ²
Cable Entry Position	Top and/or Bottom
Cable Outlets Per Side	2xM25 / 2xM25
Degree of Protection	acc. to IEC 60529 IP65
Impact Resistance Rating	Housing IK09
Enclosure Material	Aluminium
Maximum Mounted Auxiliary Contacts	1 NO, 0 NC
Mounted Auxiliary Contacts	0 NO, 0 NC
Number of Auxiliary Contacts NC	0
Number of Auxiliary Contacts NO	0
Tightening Torque	Main Circuit 1.2 N·m
Rated Current (I_n)	25 A

Technical UL/CSA

Tightening Torque

Main Circuit 1.2 N·m

Environmental

RoHS Status

Following EU Directive 2011/65/EU

RoHS Date

2009-01

Toxic Substances Control
Act - TSCA

1SCC340095D0201

Certificates and Declarations

Declaration of Conformity
- CE

1SCC340062D2702

REACH Declaration

1SCC340076D0201

Container Information

Package Level 1 Units

box 1 piece

Package Level 1 Width

112 mm

Package Level 1 Depth /
Length

131 mm

Package Level 1 Height

62 mm

Package Level 1 Gross
Weight

0.57 kg

Package Level 1 EAN

7392696424356

Classifications

Object Classification Code

Q
2CMT005069

ETIM 7

EC000216 - Switch disconnector

ETIM 8

EC000216 - Switch disconnector

ETIM 9

EC000216 - Switch disconnector (low voltage)

UNSPSC

39120000

eClass

V11.1 : 27371403

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

E-Number (Finland)

3601600

Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Switch-Disconnectors → Enclosed Switch-Disconnectors

