

LOW BAY SPECIFICATION SHEET



Lentus

Microwave sensor to save energy and cost

FEATURES

IP rating	IP65
Sensor	Microwave
Input	220-240V 50/60Hz

INSTALLATION INFORMATION

Install Connector Type	Flying lead
Construction Material	Plastic
Weight	0.20Kg
Maximum ambient temperature	70°C

WIRING INFORMATION

Cable / Flying Lead	800mm E475602 5 Core Ø8mm
Type of Wiring Required	Parallel

ACCESSORIES

HBASDHSRC	Remote controller to set up HBASDHS & LBASDHS sensors	Sold Separately
-----------	---	-----------------

PRODUCT CODES

Product code	Finish	Description
LBAS	White	Microwave sensor
LBASDHS	White	Microwave & Daylight harvesting sensor
HBASDHSRC	White	Microwave & Daylight Harvesting Sensor Controller



COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

- /collingwoodlighting
- /collingwoodlighting
- collingwoodled

GUARANTEE / WARRANTY

5 year extended guarantee

FEATURES & BENEFITS

- Standby dim level adjustable
- Standby period adjustable
- IP65 rated meaning it can be used in conditions where it may be wet
- Lighting will only turn on when it detects movement
- Ideal for aisle lighting
- Customise the dipswitches according to preference for more energy cost savings
- Customise the dimming level and enable/disable the daylight sensor
- Change the detection area on where movement is detected, along with hold time where the time period of light remains on at 100% brightness, if no further movement is detected
- Customised the dimming level and enable/disable the daylight sensor

