



WL012

IP54, 610lm straight to mains wall light

Features

IK rating	IK04
IP rating	IP54
CSP Switchable	Fixed
Tiltable	No
Dimmable Option	No
LED Lifetime	30,000h L70
CRI	80 Ra
SDCM	5 SDCM

Installation information

UK Bathroom Zone	N/A
Inrush Current	20A 0.5ms
Construction Material	Powder coated aluminium
Weight	1kg
Maximum Ambient Temperature	40°C
SELV	Yes
Electric Class (1, 2, 3)	1

Photometrics @ 25°C




Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
WL012X30	Black RAL9011	11.0W	3000K	338°	610	55	72
WL012G30	Grey RAL7022	11.0W	3000K	338°	610	55	72

Accessories

N/A	No accessories required
-----	-------------------------



01604 495 151
 collingwoodlighting.com

-  collingwoodled
-  /collingwoodlighting
-  collingwoodlighting

Guarantee

5 years

Features & benefits

- 11W
- Integral bracket for easy installation
- IP54 ideal for framing doorways and entrances
- Straight to mains screw terminals
- Durable powder coated aluminium in contemporary black or grey finish
- Provides a good light level for safe navigation at night
- Wide light distribution with 360° beam angle

Light source
 energy efficiency:



Beam angle: 338°

