



Borealis 5ft Twin

5ft Twin, LED Batten

Features

IK rating	IK06
IP rating	IP20
CSP Switchable	Fixed
UGR	26
Sensor Option	On-Off Microwave sensor & daylight switching available
Dimmable Option	Yes (DALI 2, 0-10V)
LED Lifetime	54,000h L70
CRI	80 Ra
SDCM	6 SDCM
Emergency Option	Yes

Installation information

Install Connector Type	Loop in / Loop out
Inrush Current	20A 0,2ms
Construction Material	Steel body, white powder coating PC opal diffuser
Weight	1.77Kg, EM Version: 2.03Kg
Maximum Ambient Temperature	-20°C to +40°C
SELV	Yes
UK Building Regulations	Part P
Electric Class (1, 2, 3)	1

Photometrics @ 25°C

	Finish	Feature I	Feature II	Feature III	W	Colour	Beam	lm	lm/W	lx @ 1m	EM
BT5TS40	White	54W Non-Dim	No sensor	Non emergency	54W	4000K	120°	7020	130	1894	-
BT5TS40EM	White	54W Non-Dim	No sensor	Emergency	54W	4000K	120°	7020	130	1894	250
BT5TD40	White	DALI-2 / PUSH-DIM	No sensor	Non emergency	54W	4000K	120°	7020	130	1894	-
BT5TD40EM	White	DALI-2 / PUSH-DIM	No sensor	Emergency	54W	4000K	120°	7020	130	1894	250
BT5TV40	White	1-10V	No sensor	Non emergency	54W	4000K	120°	7020	130	1894	-

Accessories

BT SK1	Suspension Kit - 2 steel wires, with holders.	Sold Separately
--------	---	-----------------



01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

5 years (product), 2 years (emerg battery)

Features & benefits

- High efficacy of 130lm/W
- Suspended gear tray for easy installation
- Emergency option available
- Multiple fixing points and several wiring options
- Flicker free
- Ideal for sheds, garages and warehouses
- MW sensing range adjustable, up to 4m high, 8m diameter
- Diffuser is released by side buttons and is easily accessible through loop-in/loop-out terminals

Light source
energy efficiency:



Beam angle: 120°

