




CONTROL GEAR

DIRECT ON-LINE STARTERS (IP65)

- 5.5kW – 11kW.

Part No.	Description	Dimensions (mm)		
		H	W	D
HUFB-11I	5.5kW / 25A / 230V coil	90	183	113
HUFB-11M	5.5kW / 25A / 400V coil	90	183	113
HUFB-18I	11kW / 32A / 230V coil	100	193	123
HUFB-18M	11kW / 32A / 400V coil	100	193	123



CONTACTORS IN A BOX

CON25 / 32

CONTACTOR	CU11-4I / CU18-4I
DESCRIPTION	4pole
THERMAL CURRENT (Ith)	25A / 32A
POWER RATING (415V)	5.5kW / 11kW
COIL VOLTAGE	230V / 50Hz
PICK UP VA	70 / 82
SEALED VA	12 / 15

CON80

CONTACTOR	CU65-22I
DESCRIPTION	3pole
THERMAL CURRENT (Ith)	80A
POWER RATING (415V)	33kW
COIL VOLTAGE	230V / 50Hz
PICK UP VA	280
SEALED VA	32



- IP55 plastic enclosure (CON25 & CON32).
- IP65 metal enclosure (CON80).
- Ideal for heating & lighting applications.

Part No.	Description	Dimensions (mm)		
		H	W	D
CON25	25A Ith 5.5kW 4pole contactor (230V coil) IP55	200	100	110
CON32	32A Ith 11kW 4pole contactor (230V coil) IP55	200	100	110
CON80	80A Ith 33kW 3pole contactor & neutral terminal (230V coil) Metal IP65	300	250	200

