



# PRODUCT DATASHEET

## LINEARLED MOBILE HANGER 270MM USB WT

Linear LED Mobile HANGER USB | Mobile luminaire for flexible mounting, with hanger, recharging via USB



### Areas of application

- For a very large range of uses
- For indoor use only
- Shelves, furniture integration or under cabinet mounting

### Product benefits

- Attractive and functional design
- Easy and quick installation

### Product features

- Integrated rechargeable lithium battery which can be charged via USB cable
- Light activated by switch or movement within 3 meters



## TECHNICAL DATA

## Electrical data

Nominal wattage	2.35 W
Nominal voltage	5 V
Mains frequency	0 Hz
Nominal current	560.000 mA
Max. number of luminaires per miniature circuit breaker C10	-
Protection class	III
Operating mode	Battery

## Photometrical data

Luminous flux	120 lm
Luminous efficacy	51 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcm
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0

## Dimensions &amp; Weight

Length	324.00 mm
Width	47.00 mm
Height	15.00 mm
Product weight	180.00 g



## Materials &amp; Colors

Product color	White
Housing color	White
Body material	Polycarbon Acrylonitrile
Cover material	Acrylonitrile butadiene styrene (ABS)

Mercury content	0.0 mg
-----------------	--------

## Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+25 °C
Type of connection	USB
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Wall
Application environment	Indoor
LED module replaceable	Not replaceable
With light source	Yes

## Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
---------------------------	-----------------------

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Sensor

Type of sensor	Motion
Sensor technology	Infrared/Photocell
Sensor controlled switching time	30 s
Detection range of motion sensor	0...3 m

## BATTERY

Type of Battery	Lithium ion
Battery size [GMS]	Others
Number of included batteries	1
Nominal voltage of battery	3.7 V
Nominal capacity of battery	1000 mAh

## Certificates & Standards

Standards	CE / EAC / UKCA
Luminaire with limited surface temperature, "D sign"	No

## EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

---

## DOWNLOAD DATA

Documents and certificates
 <a href="#">Declarations Of Conformity CE</a>

---

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075504363	Blister 1	23 mm x 140 mm x 400 mm	226.00 g	1.29 dm <sup>3</sup>
4058075504370	Shipping box 6	410 mm x 167 mm x 152 mm	1520.00 g	10.41 dm <sup>3</sup>
4058075510838	Shipping box 36	520 mm x 425 mm x 330 mm	9711.00 g	72.93 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.