

INGRESS PROTECTION MASTERSEAL PLUS PRODUCT SELECTOR

SWITCH ENCLOSURES	SWITCH MODULES	NEON MODULES	DATA/TELECOM ENCLOSURES EURO FORMAT	EURO DATA MODULES
IP66	10 AMP	20 AMP	IP66	TELECOM
				
K56420GRY	56881BLK	56889RED	K56423GRY	K5820BLK
				
K56421WHI	56882BLK	56893BLK	K56423WHI	K5821BLK
				
K56422WHI	56883BLK			
				
K56422GRY				

K56420GRY K56420WHI 1 GANG FOR USE WITH ANY ONE SWITCH MODULE	1 1	56881BLK 10A SP ONE-WAY	10	56891BLK 20A SP ONE-WAY	10	56889RED 200-250V NEON RED	10	K56423GRY K56423WHI 1 GANG DATA ENCLOSURE FOR 2 MODULE EURO OUTLET	1 1	K5820WHI K5820BLK TELEPHONE MASTER ONE MODULE	5 5
K56421GRY K56421WHI 1 GANG WITH NEON FOR USE WITH ANY SWITCH AND ANY NEON MODULE	1 1	56882BLK 10A SP TWO-WAY	10	56892BLK 20A SP TWO-WAY	10	56893BLK 20A INTERMEDIATE	10	K5821WHI K5821BLK TELEPHONE SECONDARY ONE MODULE	5 5		
K56422GRY K56422WHI 2 GANG FOR USE WITH ANY TWO SWITCH MODULES	1 1	56883BLK 10A DP ONE-WAY	10	56896BLK 20A DP ONE-WAY	10			2 data modules can be accommodated providing care is used to ensure that the cables are correctly routed through the outlet. Fixing holes are for No.8 woodscrews (not supplied). Backbox has 4 x 20mm entries, 1 on each edge. Supplied with an earth terminal and a loop terminal in the backbox. DIMENSIONS 160 x 117 x 89mm IP66 to BS EN 60529:1992+A2:2013		DIMENSIONS 25 x 50mm BS 6312-2	
Fixing holes are for No.8 woodscrews (not supplied). Each enclosure is fitted with a neon which should be wired as a locator. The enclosure has 4 x 20mm entries, 1 on top, bottom and each side and is supplied with an earth terminal and a loop terminal in the back box. NOTE These enclosures are for use with the Masterseal Plus™ switch and neon modules. DIMENSIONS 95 x 95 x 57mm IP66 to BS EN 60529:1992+A2:2013		For use only with Masterseal Plus™ switch enclosures. These switches do NOT have to be derated when used with fluorescent or inductive loads. BS EN 60669-1:2018		For use only with Masterseal Plus™ switch enclosures. These switches do NOT have to be derated when used with fluorescent or inductive loads. BS EN 60669-1:2018							

INGRESS PROTECTION MASTERSEAL PLUS PRODUCT SELECTOR

EURO DATA MODULES	JUNCTION BOXES	FLUSH MOUNTING FRAMES	FLUSH MOUNTING BEZELS	CONDUIT ENTRIES	ACCESSORIES
DATA  K5844WHI	30 AMP IP66  K56506GRY	 K56500GRY	 K56502GRY	 56460WHI  56461WHI	 MK9933
 K5887WHI	 K56506WHI (COVER ON)	 56500WHI	 56502WHI	 56462WHI  56463WHI	 56890GRN
 K5887BLK	 K56506WHI (COVER OFF)	 K56501GRY	 K56503GRY	 56464WHI	

K5844WHI	5	K56506GRY	1	K56500GRY	1	K56502GRY	1	K5660GRY	1
RJ45 CAT 5e ANGLED UNSCREENED ONE MODULE		K56506WHI	1	K56500WHI	1	K56502WHI	1	MK9933	1
K5887WHI	5	K56506BLK	1	1 GANG		FLUSH MOUNTING BEZEL FOR USE WITH 160 X 117MM PRODUCTS		M20 EARTH LEAD ADAPTOR FOR EARTHING METAL CONDUIT	
K5887BLK	5	JUNCTION BOX WITH FOUR 4-WAY TERMINALS		PLASTER/TILE FLUSH MOUNTING FRAME WITH PROTECTIVE COVER FOR USE WITH 160 X 117MM PRODUCTS		56502GRY	1	56460WHI	5
RJ11/12 ONE MODULE				56500GRY	1	56502WHI	1	ENTRY BLANK	
		Fixing holes are for No. 8 woodscrews (not supplied). The enclosure has 4 entries, 1 on top, bottom and both sides.		56500WHI	1	1 GANG FLUSH MOUNTING BEZEL FOR USE WITH 95 X 95MM SWITCHES		56461BLK	
K5844		TERMINAL CAPACITY Each terminal block accepts four 2.5mm ² cables.		1 GANG PLASTER/TILE FLUSH MOUNTING FRAME WITH PROTECTIVE COVER FOR USE WITH 95 X 95MM SWITCHES		K56503GRY	1	56461WHI	5
Enhanced Cat 5e performance. Suitable for both 568A and 568B wiring schemes.		DIMENSIONS 95 x 95 x 65mm BS EN60670-22:2006 and BS EN 60670-1:2005+A1:2013 IP66 to BS EN 60529:1992+A2:2013		K56501GRY	1	K56503WHI	1	PVC CABLE ENTRY TO PROVIDE DIRECT ENTRY OF POWER CABLE TO THE UNIT VIA THE BOTTOM BOX ENTRY	
ISO/IEC 11801 EN 50173 TIA 568 EN 41003				K56501WHI	1	The Flush adapters for brick and cavity walls should be used on vertical surfaces where no additional finishing, such as plastering is required. Allows flush mounted Masterseal Plus™ products to maintain their IP rating. Can only be used with back entry enclosures. Supplied with 4 self tapping screws to fix enclosure to mounting bezel. Clip-on surround hides mounting screws.		56462BLK	5
K5887				2 GANG PLASTER/TILE FLUSH MOUNTING FRAME WITH PROTECTIVE COVER		DIMENSIONS 56502 145 x 145 x 41mm K56502 165 x 165 x 41mm K56503 165 x 245 x 41mm		56462WHI	5
Suitable for both RJ11 and RJ12 jacks								20MM PLAIN CONDUIT ENTRY PUSH FIT ADAPTOR BETWEEN BACK BOX AND 20MM PLAIN CONDUIT	
RJ11 4 wire RJ12 6 wire								56463BLK	5
FCC68 EN 41003								56463WHI	5
DIMENSIONS 25 x 50mm								20MM THREADED CONDUIT ENTRY PUSH FIT ADAPTOR BETWEEN BACK BOX AND 20MM THREADED CONDUIT	
								56464BLK	5
								56464WHI	5
								BOX COUPLER FOR GANGING ONE MASTERSEAL PLUS™ BOX NEXT TO ANOTHER	