

Toggle Switch Modules

Grid Plus Modular Frontplates

SUPPLIED WITH GRIDS

20 AMP
SP 1 WAY20 AMP
SP 2 WAY20 AMP
DP 1 WAY20 AMP
INTERMEDIATE

1 MODULE



FINISHES

BRUSHED STAINLESS STEEL	K14891BSS	1	K14892BSS	1	K14896BSS	1	K14893BSS	1	K14331BSS	1
LACQUERED BRUSHED STEEL	K14891LBS	1	K14892LBS	1	K14896LBS	1	K14893LBS	1	K14331LBS	1
SILVER ANODIZED ALUMINIUM	K14891SAA	1	K14892SAA	1	K14896SAA	1	K14893SAA	1	K14331SAA	1
BRUSHED CHROME	K14891BRC	1	K14892BRC	1	K14896BRC	1	K14893BRC	1	K14331BRC	1
POLISHED CHROME	K14891POC	1	K14892POC	1	K14896POC	1	K14893POC	1	K14331POC	1
SATIN GOLD	K14891SAG	1	K14892SAG	1	K14896SAG	1	K14893SAG	1	K14331SAG	1
PORCELAIN WHITE	K14891WHI	1	K14892WHI	1	K14896WHI	1	K14893WHI	1	K14331WHI	1
LUSTROUS WHITE	K14891LIV	1	K14892LIV	1	K14896LIV	1	K14893LIV	1	K14331LIV	1
LUSTROUS BLACK	K14891LBK	1	K14892LBK	1	K14896LBK	1	K14893LBK	1	K14331LBK	1
POLISHED BRASS	K14891PBR	1	K14892PBR	1	K14896PBR	1	K14893PBR	1	K14331PBR	1
TEXTURED IRON	K14891TIR	1	K14892TIR	1	K14896TIR	1	K14893TIR	1	K14331TIR	1
DESERT BRONZE	K14891DBZ	1	K14892DBZ	1	K14896DBZ	1	K14893DBZ	1	K14331DBZ	1
ANTIQUE BRASS	K14891ABS	1	K14892ABS	1	K14896ABS	1	K14893ABS	1	K14331ABS	1
TEXTURED COPPER	K14891TCO	1	K14892TCO	1	K14896TCO	1	K14893TCO	1	K14331TCO	1

LEAD TIMES: Please contact our Customer Services Department on: 01268 563 404

These switches do NOT have to be derated when used with fluorescent and inductive loads.
BS EN 60699-1: 1999

These switches do NOT have to be derated when used with fluorescent and inductive loads.
BS EN 60699-1: 1999

These switches do NOT have to be derated when used with fluorescent and inductive loads.
BS EN 60699-1: 1999

These switches do NOT have to be derated when used with fluorescent and inductive loads.
BS EN 60699-1: 1999

MOUNTING BOX
FLUSH: 891ALM
DIMENSIONS:
86 x 86mm
BS 5733: 2010