



ESC426

**Contactors 25A, 4NC, 230V~50Hz**

**Technical characteristics**

**Architecture**

Number of poles	4 P
-----------------	-----

**Main electrical features**

Rated operational voltage Ue	400 V
Frequency	50 Hz

**Voltage**

Rated insulation voltage	440 V
Rated impulse withstand voltage	4 kV

**Dimensions**

Depth of installed product	60 mm
Height of installed product	83 mm
Width of installed product	35.75 mm

**Power**

Total power loss under IN	6 W
Power dissipation per coil	1.5 W

**Endurance**

Electric endurance in number of cycles	30000
Number of mechanical operations	1000000

**Fluorescent bulbs control**

Max. power with fluorescent parallel lamps	810 VA
--	--------

**Incandescent bulbs control**

Max. power with incandescent lamps	1900 W
------------------------------------	--------

**Connection**

Connection cross-sect. flexible conductor	1 / 6mm <sup>2</sup>
Type of connection	with screw
Number of contacts	4

**Equipment**

Can be accessorized	Yes
---------------------	-----

**Standards**

European directive WEEE	concerned
-------------------------	-----------

**Safety**

Protection index IP	IP2X
Protection class	isol.class II
<b>Use conditions</b>	
Operating temperature	-10...50 °C