



EEK523P

## Pluggable Digital PIR Occupancy Sensor 3 meter lead

### Technical characteristics

#### Architecture

|             |                |
|-------------|----------------|
| Bus system  | Without        |
| Fixing mode | flush-mounting |

#### Main electrical features

|           |          |
|-----------|----------|
| Frequency | 50/60 Hz |
|-----------|----------|

#### Power supply

|                |                   |
|----------------|-------------------|
| Supply voltage | 230 V +10% / -15% |
|----------------|-------------------|

#### Detection

|                 |       |
|-----------------|-------|
| Detection angle | 360 ° |
|-----------------|-------|

#### Materials

|                           |                       |
|---------------------------|-----------------------|
| Colour                    | white                 |
| RAL colour                | RAL 9010 - Pure white |
| Material                  | thermoplastic         |
| Type of surface treatment | untreated             |

#### Lighting control

|                              |              |
|------------------------------|--------------|
| Brightness measurement range | 5 / 1000 Lux |
|------------------------------|--------------|

#### Installation, mounting

|                         |       |
|-------------------------|-------|
| Maximum Mounting Height | 3.5 m |
|-------------------------|-------|

#### Equipment

|                               |       |
|-------------------------------|-------|
| Angle of horizontal detection | 360 ° |
|-------------------------------|-------|

#### Safety

|                     |               |
|---------------------|---------------|
| Protection index IP | IP41          |
| Protection class    | isol.class II |