

Technical Data Sheet

CODE 11976

ARIETT T



Certifications



TECHNICAL AND PERFORMANCE DATA

Frequency (Hz)	50	Voltage (V)	230
Insulation class	II°	Weight (Kg)	1,40
IP	X4	Max airflow (l/s)	19,4
Max absorbed current (A)	0,14	Max airflow (m³/h)	70
Max absorbed power (W)	18	Max pressure (mmH2O)	12
Max ambient temperature for continuous operation (°C)	40	Max pressure (Pa)	118
Nominal diameter (mm)	100	RPM	2315
Ø Discharge hole (mm)	97	Sound pressure Lp [dB (A)] at 3 m	40

DIMENSIONS

Size A (mm)	156
Size B (mm)	123
Size C (mm)	25
Size D (mm)	Ø 97
Size E (mm)	60
Size F (mm)	60

PER INFORMAZIONI / FOR INFORMATION

ITALY

Pre Sales:

prevendita@vortice-italy.com

After Sales:

postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF

IRELAND

Sales Dept:

sales@vortice.ltd.uk

Technical Dept:

technical@vortice.ltd.uk

OTHER COUNTRIES

Sales Dept:

export@vortice-italy.com

After Sales:

after-sales@vortice-italy.com

Technical Data Sheet

CODE 11976

ARIETT T



DESCRIPTION

PER INFORMAZIONI / FOR INFORMATION

ITALY

Pre Sales:
prevendita@vortice-italy.com
After Sales:
postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF IRELAND

Sales Dept:
sales@vortice.ltd.uk
Technical Dept:
technical@vortice.ltd.uk

OTHER COUNTRIES

Sales Dept:
export@vortice-italy.com
After Sales:
after-sales@vortice-italy.com