



17W LED CEILING/WALL LIGHT

- Polycarbonate construction
- Visually similar, energy efficient alternative to 28W 2D fittings
- Multiple low power LED array & optically optimised diffuser: ensures a soft lighting effect with no degradation of light output

LI-ION EMERGENCY VERSIONS:

- 3hr maintained emergency lighting: also available in non-emergency options
- Facility for non-maintained mode
- Battery - Li-Ion 3.2V 1500mAh • Battery 1 year warranty - Replacement battery code: EB11

MICROWAVE SENSOR VERSIONS:

- Adjustable detection angle: up to 150°
- Adjustable detection range: Max. 4-6m at 3m installation height
- Adjustable time setting: 5 seconds - 30 minutes
- Adjustable Lux control: 2/10/25/50 lux or disable
- Detection is possible through doors, glass panels & thin walls



LED LAMP SPECIFICATIONS:	
Luminaire lumens (with diffuser)	1843 lm
Lumens from chip (no diffuser)	2143 lm
Useful lumens	1668 lm
Rated Wattage	17W
Rated luminous flux	1668 lm
Nominal life time of the lamp	50,000 hrs
Colour temperature	4000K
Number of switching cycles before premature lamp failure	≥15,000
Warm-up time up to 60% of the full light output	Instant full light
Dimmable	No
Nominal beam angle	120°
Rated power	17W
Rated lamp lifetime	50,000 hrs
Displacement factor	≥0.8
Lumen maintenance factor at end of nominal life	≥0.8
Starting time	<0.1s
Colour rendering	≥80
Colour consistency	Within a six step Macadam ellipse
Rated peak intensity	545cd
Rated beam angle	120°
Voltage / Frequency	240V~50Hz
Lumen efficacy: 98 lm / W	
This product contains a Light Source of Energy Efficiency Class E	
Not suitable for accent lighting	



5

Year Warranty



Emergency Product



Li-Ion Battery



IP65



Microwave Sensor



✔ IES Files



Earthed

Code	Version	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating	MOM / OPQ
CFLEDWHSC	Standard	17W	4000K	1843 lm	50,000 hrs	IP65	1 / 8
MSLEDWHSC	MW						
CFLWHEM3SC	EM3						
MSLWHEM3SC	MW + EM3						

