

ORBIX STANDARD WOOD SCREW

USE FOR

- ➕ Direct fixing into wood
- ➕ Direct fixing into standard wallplug



Key Feature:

Extra sharp tip for faster installation.
Countersunk head.

ORBIX PAN HEAD

USE FOR

- ➕ Where space is tight – a range of self-drilling screws with a smaller diameter head.

Key Feature:

Every screw has a **BRAND NEW DRILL BIT** – built in! Always sharp, always the right size.



ORBIX-WS

Available in a wide range of sizes



Features/Benefits:

- ✓ Strong reliable fixing for wood and wallplugs
- ✓ Specially designed profile thread for quick assembly and long-lasting hold
- ✓ Wax coat for faster, easier installation saving energy

3.0mm Dia.

OBX-WS-3.0x20 (200pk)
OBX-WS-3.0x25 (200pk)

3.5mm Dia.

OBX-WS-3.5x20 (200pk)
OBX-WS-3.5x25 (200pk)
OBX-WS-3.5x30 (200pk)

4.0mm Dia.

OBX-WS-4.0x40 (200pk)
OBX-WS-4.0x50 (200pk)

4.5mm Dia.

OBX-WS-4.5x25 (200pk)
OBX-WS-4.5x40 (200pk)
OBX-WS-4.5x50 (200pk)

5.0mm Dia.

OBX-WS-5.0x60 (100pk)
OBX-WS-5.0x75 (100pk)

Application:

- ➕ Fixing electrical accessories into solid wood, timber panels or laminated timber

DS-PAN-4.2 x13

Steel thickness:
Up to 2.5mm



DS-PAN-4.8 x20

Steel thickness:
Up to 3.0mm



Features/Benefits:

- ✓ Self drilling/self tapping into metal
- ✓ No nuts, bolts, spanners etc.
- ✓ No changing drill/drive bits
- ✓ Can be removed and re-used
- ✓ Point caps available to protect cables when installed
- ✓ Available in large 'trade packs'

Application:

- ➕ Fixing clips/cleats/saddles etc. to metal where the standard Orbix head would be too big.
- ➕ **PLUS ENDLESS APPLICATIONS THAT REQUIRE A FAST, ONE-SHOT JOINING OF THIN STEEL**