ORBIX STANDARD WOOD SCREW

USE FOR

- Direct fixing into wood
- Direct fixing into standard wallplug

Key Feature:

Extra sharp tip for faster installation.

Countersunk head.

OBX-WS

Available in a wide range of sizes

3.0mm Dia.
OBX-WS-3.0x20 (200pk)
OBX-WS-3.0x25 (200pk)

3.5mm Dia.
OBX-WS-3.5x20 (200pk)
OBX-WS-3.5x25 (200pk)
OBX-WS-3.5x30 (200pk)

4.0mm Dia.
OBX-WS-4.0x40 (200pk)
OBX-WS-4.0x50 (200pk)

4.5mm Dia.
OBX-WS-4.5x25 (200pk)
OBX-WS-4.5x40 (200pk)
OBX-WS-4.5x50 (200pk)

5.0mm Dia.
OBX-WS-5.0x60 (100pk)
OBX-WS-5.0x75 (100pk)

Features/Benefits:

- Strong reliable fixing for wood and wallplugs
- Specially designed profile thread for quick assembly and long-lasting hold
- Wax coat for faster, easier installation saving energy

Application:

- Fixing electrical accessories into solid wood, timber panels or laminated timber

ORBIX PAN HEAD

USE FOR

- Where space is tight – a range of self-drilling screws with a smaller diameter head.

Key Feature:

Every screw has a **BRAND NEW DRILL BIT** – built in! Always sharp, always the right size.

DS-PAN-4.2 x13

Steel thickness:
Up to 2.5mm

DS-PAN-4.8 x20

Steel thickness:
Up to 3.0mm

Features/Benefits:

- Self drilling/self tapping into metal
- No nuts, bolts, spanners etc.
- No changing drill/drive bits
- Can be removed and re-used
- Point caps available to protect cables when installed
- Available in large 'trade packs'

Application:

- Fixing clips/cleats/saddles etc. to metal where the standard Orbix head would be too big.
- **PLUS ENDLESS APPLICATIONS THAT REQUIRE A FAST, ONE-SHOT JOINING OF THIN STEEL**