

**IP44
SPLASHPROOF
100 - 130V
50 - 60 Hz**

Plugs



Connectors

Socket Outlets
ANGLED

SURFACE



SURFACE – LOOP IN



STRAIGHT

PANEL MOUNTING



Amps Pin.
Config-
uration Earth
Hour
Pos

16	2P+E	4	K9000YEL	K9100YEL	K9200YEL	K13200YEL	K9400YEL
16	3P+E	4	K9005YEL	K9105YEL	K9205YEL		K9405YEL
16	3P+N+E	4	K9013YEL	K9113YEL	K9213YEL		K9413YEL
32	2P+E	4	K9032YEL	K9132YEL	K9232YEL	K13232YEL	K9432YEL
32	3P+E	4		K9135YEL	K9235YEL		
32	3P+N+E	4	K9043YEL	K9142YEL	K9239YEL		

Fitted with
cable entry gland.
BS EN 60309

Fitted with
cable entry gland.
BS EN 60309

16A Top conduit (M20) or
rear cable entry, complete
with blanking plug.
32A Top conduit (M25) or
rear cable entry, complete
with blanking plug.
BS EN 60309

Suitable for top entry
2 x Ø25.
Fitted with terminals
for Loop In 2 x 10mm².
BS EN 60309

All flanges have the same
fixing centres and outside
dimensions to assist panel
builders.
Minimised flange option
available (see page 258).
BS EN 60309

**IP67
WATERTIGHT
100 - 130V
50 - 60 Hz**

Plugs



Connectors



Socket Outlets

ANGLED

SURFACE



SURFACE – LOOP IN



PANEL MOUNTING



Amps Pin.
Config-
uration Earth
Hour
Pos

16	2P+E	4	K9023YEL	K9123YEL	K9193YEL	K13023YEL	K9802YEL
32	2P+E	4	K9053YEL	K9155YEL	K9761YEL	K13053YEL	K9865YEL
63	2P+E	4	K9294YEL	K9855YEL			

Suitable for flexible cable only.
63A: with external clamp.
BS EN 60309

Suitable for flexible cable only.
63A: with external clamp.
BS EN 60309

Suitable for top entry 2 x Ø25
or bottom entry 2 x Ø20.
Will accept FL13 flange at top.
BS EN 60309

Suitable for top entry 2 x Ø25
BS EN 60309

All flanges have the same
fixing centres and outside
dimensions to assist panel
builders.
BS EN 60309

**IP44
SPLASHPROOF
100 - 130V
50 - 60 Hz
16 Amps
2P+E**

Socket Outlets

TWIN

SURFACE

Prewired Unwired
K13143YEL **K13043YEL**



Suitable for top entry 2 x Ø25 2 x Ø38
Bottom entry 3 x 47.5mm
BS EN 60309

63A plugs and inlets include pilot pins.

63A connectors and sockets with pilot sleeves are available to special order.

All products are available in minimum order quantity of one except K9000 and K9100
(which have a minimum order quantity of 10).

Photographs feature the most representative products.
Design changes may occur (over different current ratings) from one product to another.