



ALBANY PLUS™

RANGE INTRODUCTION

Available in Brushed Stainless Steel, Brushed Chrome, Satin Gold and Polished Chrome finishes, Albany Plus™ brings stylish yet subtle good looks to both contemporary and classical interiors.

Being manufactured from the finest materials, Albany Plus™ wiring devices maintain their high quality appearance for years to come.

Echo™ is an innovative range of entirely wireless, batteryless and self powered switches, only available from MK Electric and in finishes to complement the Albany Plus™ range. Please see page 21 for details.

HOW TO SPECIFY

A metal, flush mounting range of wiring devices. Frontplates with a maximum 9mm profile and subtle 7mm radius rounded corners. Cable connections must be upward facing with easy to identify white markings on a dark background, grouped in a straight line with captive terminal screws for ease of installation. All sockets to have a 3 pin operated shutter safety mechanism and double pole switching, with the contacts designed such that the neutral makes before and breaks after the live pole for improved safety. Switches to be large and concave with a minimum 3mm contact gap with a positive 'click' to denote successful operation.

FEATURES & BENEFITS

AVAILABLE IN BRUSHED STAINLESS STEEL, BRUSHED CHROME, SATIN GOLD AND POLISHED CHROME

Providing a range of products that complement the décor and requirements of any interior.

ALBANY PLUS™ BRUSHED CHROME AND SATIN GOLD ARE PRE-TREATED WITH A HEAT-CURED POWDER LACQUER FINISH

Brushed Chrome and Satin Gold products are coated with a special heat-cured powder lacquer finish ensuring that the range is durable, tarnish resistant and maintains its stylish and understated appearance for many years.

TOTAL SAFETY

MK sockets have a 3-pin operated "child resistant shutter system", which is designed to inhibit access to the electricity supply unless all 3 pins of a standard British 13A plug are in position.

DESIGN SERVICE

Perfect for when only a customised solution will do.

Albany Plus™

mkelectric.co.uk



DOUBLE POLE
SWITCHING

MATCHING
SCREWS

STYLISH CURVED DESIGN
Blends unobtrusively into the
environment

3-PIN "CHILD RESISTANT SHUTTER
SYSTEM"
Designed to inhibit access to the
electricity supply, unless all 3 pins of a
standard British 13A plug are in position

PRE-TREATED HEAT-CURED POWDER
LACQUER FINISH (BRC AND SAG)
Ensures that the range is durable and
tarnish resistant

Terminal screws are backed out
and captive. Terminals are upwards
facing to make installation easier.

Funnel entrance to terminals.

Clear terminal markings for easy
identification.

Polished Chrome finish
complements modern
interior design.

Brushed Chrome finish has subtle good looks to suit
classic interiors.



Albany Plus™

mkelectric.co.uk



Switchsocket Outlets

1 GANG DP
ROUND PIN
15 AMP



Switchsocket Outlets RCD Protected

1 GANG DP 30MA
RATED TRIPPING
CURRENT ACTIVE
CONTROL CIRCUIT
13 AMP



1 GANG DP 30MA
RATED TRIPPING
CURRENT PASSIVE
CONTROL CIRCUIT
13 AMP



Socket Outlets

1 GANG
13 AMP



2 GANG WITH
DUAL EARTH
TERMINALS
13 AMP



FINISHES

BRUSHED STAINLESS STEEL	K2883BSS	5	K6301BSS	1	K6304BSS	1	K732BSS	5	K733BSS	5
BRUSHED CHROME	K2883BRC	1	K6301BRC	1	K6304BRC	1	K732BRC	1	K733BRC	1
SATIN GOLD	K2883SAG	1	K6301SAG	1						
POLISHED CHROME	K2883PCR	5	K6301PCR	1						

LEAD TIMES
Please contact our Customer
Services Department on
01268 563 404

MOUNTING BOXES
FLUSH 25MM
861ZIC
FLUSH 35MM
(for extra wiring space)
866ZIC
SURFACE WITH KNOCKOUTS
K899ALM
SURFACE WITHOUT
KNOCKOUTS
K829ALM
DIMENSIONS
86 x 86mm
FIXING CENTRES
60.3mm
BS 546:1950

MOUNTING BOXES
FLUSH
886ZIC
Boxes must have a minimum
depth of 30mm
SURFACE WITH KNOCKOUTS
K897ALM
SURFACE WITHOUT
KNOCKOUTS
K830ALM
It is important to ensure that
the correct control circuit,
active or passive, is selected
for each application.
Only suitable for supply
voltage of 240V a.c.
DIMENSIONS
86 x 146mm
FIXING CENTRES
120.6mm
BS 7288:1990

MOUNTING BOXES
FLUSH 35MM
2 gang: 886ZIC
FLUSH 46MM
(for extra wiring space)
2 gang: 877ZIC
SURFACE WITH KNOCKOUTS
2 gang: K897ALM
SURFACE WITHOUT
KNOCKOUTS
2 gang: K830ALM
DIMENSIONS
86 x 146mm
FIXING CENTRES
120.6mm
It is important to ensure that
the correct control circuit,
active or passive, is selected
for each application.
Only suitable for supply
voltage of 240V a.c.
BS 7288:1990

MOUNTING BOXES
FLUSH 25MM
1 gang: 861ZIC
FLUSH 35MM
(for extra wiring space)
1 gang: 866ZIC
SURFACE WITH KNOCKOUTS
1 gang: K899ALM
SURFACE WITHOUT
KNOCKOUTS
K829ALM
DIMENSIONS
86 x 86mm
FIXING CENTRES
60.3mm
BS 1363-2:1995

MOUNTING BOXES
FLUSH 25MM
2 gang: 862ZIC
FLUSH 35MM
(for extra wiring space)
2 gang: 886ZIC
SURFACE WITH KNOCKOUTS
2 gang: K897ALM
SURFACE WITHOUT
KNOCKOUTS
2 gang: K830ALM
DIMENSIONS
86 x 146mm
FIXING CENTRES
120.6mm
BS 1363-2:1995
HIGH INTEGRITY EARTHING
Fitted with two earth
terminals to provide a
double earth facility for use
when installations require
a high integrity protective
connection as specified within
BS 7671:2008