

Shaver/
Toothbrush
Supply Outlet

DUAL VOLTAGE
115/230V OUTPUT
220/240V
50/60Hz INPUT

Connection Units
Switched

DP
13 AMP

DP
WITH NEON
13 AMP

DP WITH
NEON &
FLEX OUTLET
13 AMP

Connection Units
Unswitched

WITH NEON
13 AMP



FINISHES

BRUSHED STAINLESS STEEL	K24709BSS*	1	K24941BSS*	1	K24961BSS*	1	K24971BSS*	1	K24958BSS*	1
LACQUERED BRUSHED STEEL	K24709LBS*	1	K24941LBS*	1	K24961LBS*	1	K24971LBS*	1	K24958LBS*	1
BRUSHED CHROME	K24709BRC*	1	K24941BRC*	1	K24961BRC*	1	K24971BRC*	1	K24958BRC*	1
POLISHED CHROME	K24709POC*	1	K24941POC*	1	K24961POC*	1	K24971POC*	1	K24958POC*	1
SATIN GOLD	K24709SAG*	1	K24941SAG*	1	K24961SAG*	1	K24971SAG*	1	K24958SAG*	1
PORCELAIN WHITE	K24709WHIW	1	K24941WHIW	1	K24961WHIW	1	K24971WHIW	1	K24958WHIW	1
	K24709LIVW	1	K24941LIVW	1	K24961LIVW	1	K24971LIVW	1	K24958LIVW	1
LUSTROUS BLACK	K24709LBKB	1	K24941LBKB	1	K24961LBKB	1	K24971LBKB	1	K24958LBKB	1
POLISHED BRASS	K24709PBR*	1	K24941PBR*	1	K24961PBR*	1	K24971PBR*	1	K24958PBR*	1
TEXTURED IRON	K24709TIRB	1	K24941TIRB	1	K24961TIRB	1	K24971TIRB	1	K24958TIRB	1
DESERT BRONZE	K24709DBZB	1	K24941DBZB	1	K24961DBZB	1	K24971DBZB	1	K24958DBZB	1
ANTIQUÉ BRASS	K24709ABSB	1	K24941ABSB	1	K24961ABSB	1	K24971ABSB	1	K24958ABSB	1
TEXTURED COPPER	K24709TCOB	1	K24941TCOB	1	K24961TCOB	1	K24971TCOB	1	K24958TCOB	1

LEAD TIMES: Please contact our Customer Services Department on: 01268 563 404

* Available with the option of either White or Black inserts. Add Suffix 'W' or 'B' to part number when ordering, E.g. KxxxxBSSW.

Where there is no asterisk, the final suffix W = White Insert, B = Black Insert, E.g. KxxxxWHIW = Porcelain White finish with White inserts

MOUNTING BOXES:
FLUSH: 878ZIC

This design incorporates a double wound isolating transformer rated 20VA at 230 or 115 volts and meets BS EN 61558-2-5: 1998 making it safe for use in bathrooms.

Insertion of a shaver/toothbrush plug automatically switches on by energising the primary side of the isolating transformer – removal automatically switches off. The transformer is protected against overload by an automatic solid state overload device with automatic resetting.

DIMENSIONS:
146 x 86mm

FIXING CENTRES: 120.6mm
BS EN 61558-2-5: 1998

MOUNTING BOXES:
FLUSH: 877ZIC

All connection units are fitted with a 13A fuse (to BS 1362).

TERMINAL CAPACITY:
2 x 6mm² stranded (max)

DIMENSIONS:
86 x 86mm

FIXING CENTRES:
60.3mm

BS 1363-4: 1995

Neon is only available in white or black insulated rocker.

Matching metal capped fuse carriers are standard on all Aspect Connection Units (except Black and White).