

# LED Floodlight

## Available wattages:




## Product features:

- Robust PDC aluminium housing
- Frosted glass diffuser
- Full IP65 construction including sensor
- PIR sensor option available
- 0.75m fly-wire cable as standard



Power (W)	10W	10W PIR	20W	20W PIR	30W	30W PIR	50W	50W PIR
Lumens	850 lm	850 lm	1700 lm	1700 lm	2550 lm	2550 lm	4250 lm	4250 lm
CCT (K)	4000 K	4000 K	4000 K	4000 K	4000 K	4000 K	4000 K	4000 K
Beam Angle	Symmetrical wide	Symmetrical wide	Symmetrical wide	Symmetrical wide	Symmetrical wide	Symmetrical wide	Symmetrical wide	Symmetrical wide
Order code	911401854485	911401854585	911401854685	911401854785	911401854885	911401854985	911401855085	911401855185



IP65



35,000 hours



3 years warranty



IK06



Operating temp  
-40° to +50°



750mm cable length

Power (W)	10W	10W PIR	20W	20W PIR	30W	30W PIR	50W	50W PIR
A (mm)	107	107	140	140	185	185	223	223
B (mm)	102	137	125	153	161	183	183	210
C (mm)	28	58	29	54	28	56	31	57