

technical hotline +44 (0)1268 563720

decorative | wiring devices

2 GANG DP
WITH
CLEAN EARTH
FACILITY
FLUSH

2 GANG DP
FILTERED
13 AMP
SPIKE AND RFI
FLUSH

REPLACEMENT
FILTER SOCKET

1 GANG DP
5 AMP
SHUTTERED
ROUND PIN
FLUSH

1 GANG DP
15 AMP
SHUTTERED
ROUND PIN
FLUSH

Switchsocket
Outlets RCD
Protected
1 GANG
30MA RATED
TRIPPING CURRENT
ACTIVE CONTROL
CIRCUIT FLUSH



K1259BSS	5	K2826BSS	5	K1800WHI	5	K2881BSS	10	K2883BSS	10		
K1259BRC	5	K2826BRC	5			K2881BRC	10	K2883BRC	10	K6301BRC	5
K1259SAG	5	K2826SAG	5			K2881SAG	10	K2883SAG	10		
K1259PCR	5	K2826PCR	5			K2881PCR	10	K2883PCR	10		

K1258, K1259,
These products are
provided with facilities for
'clean earth' connection
and are suitable for non
standard plugs with 'T'
shaped earth pin.
See page 224.

BS 1363 Pt 2: 1995
where relevant

MOUNTING BOX: 866ZIC
Provides two way filtering
to reduce voltage spikes and
radio frequency interference.
Protected by thermal cut out.
Fitted with two earth
terminals to provide a
double earth facility when
installations require a
high integrity protective
connection as specified
within BS 7671: 2008.
Maximum total load 13A
DIMENSIONS:
86 x 146 x 39mm
FIXING CENTRES:
120.6mm
BS 5733: 2010

Maximum total load is
13A
BS 5733: 2010

MOUNTING BOXES:
FLUSH 25mm: 861ZIC
FLUSH 35mm: (for extra
wiring space) 866ZIC
SURFACE (BRC)
WITH KNOCKOUTS: K899ALM
WITHOUT KNOCKOUTS:
K829ALM
DIMENSIONS: 86 x 86mm
FIXING CENTRES: 60.3mm
BS 546: 1950

MOUNTING BOXES:
FLUSH 25mm: 861ZIC
FLUSH 35mm: (for extra
wiring space) 866ZIC
SURFACE (BRC)
WITH KNOCKOUTS:
K899ALM
WITHOUT KNOCKOUTS:
K829ALM
DIMENSIONS: 86 x 86mm
FIXING CENTRES: 60.3mm
BS 546: 1950

MOUNTING BOXES
FLUSH: 886ZIC
Boxes must have a minimum depth
of 30mm
SURFACE (BRC)
WITH KNOCKOUTS: K897ALM
WITHOUT KNOCKOUTS: K830ALM
It is important to ensure that
the correct control circuit, active
or passive, is selected for each
application.
Only suitable for supply voltage of
240V a.c., 50Hz.
DIMENSIONS: 86 x 146mm
FIXING CENTRES: 120.6mm
BS 7288: 1990