

Switchsocket Outlets

Appliance Inlets

ANGLED
PANEL MOUNTING

ANGLED
INTERLOCKED
SURFACE

ANGLED
SURFACE



Amps	Pin. Configuration	Earth			
16	2P+E	6	K9771BLU	K73601BLU	K9701BLU
16	3P+E	9		K9601BLU	
16	3P+N+E	9		K9607BLU	
32	2P+E	6	K9774BLU	K73633BLU	K9733BLU
32	3P+E	9		K9633BLU	
32	3P+N+E	9		K9639BLU	
63	2P+E	6		K9306BLU	

16/32A
new range has different fixing centres to old range.
Old range is available for limited period. See technical section for details
BS EN 60309

Switch can be locked in open or closed position.
Suitable for top entry 2 x M32 or 2 x M40 or bottom entry 2 x M32 or 2 x M40
BS EN 60309

16A Top conduit (M20) or rear cable entry, complete with blanking plug.
32A Top conduit (M25) or rear cable entry, complete with blanking plug
BS EN 60309

Switchsocket Outlets

ANGLED
INTERLOCKED
SURFACE



Amps	Pin. Configuration	Earth	
16	2P+E	6	K73624BLU
16	3P+E	9	
32	2P+E	6	K73654BLU
32	3P+E	9	
63	2P+E	6	

Switch can be locked in open or closed position.
Suitable for top entry 1 x M20 and 1 x M25 or bottom entry 1 x M20 and 1 x M25
BS EN 6030