

Floor Mounted Euro Frames

1 GANG
STANDARD



2 GANG
STANDARD



Key Operated Socket Outlet and Switch

KEY OPERATED
1 GANG DP
DUAL EARTH
13 AMP



KEY OPERATED
1 GANG
DP SWITCH
20 AMP



FINISHES					
BRUSHED STAINLESS STEEL	K14790BSS	1	K14791BSS	1	K14355BSS* 1
LACQUERED BRUSHED STEEL	K14790LBS	1	K14791LBS	1	K14355LBS* 1
SILVER ANODIZED ALUMINIUM	K14790SAA	1	K14791SAA	1	K14355SAA* 1
BRUSHED CHROME	K14790BRC	1	K14791BRC	1	K14355BRC* 1
POLISHED CHROME	K14790POC	1	K14791POC	1	K14355POC* 1
SATIN GOLD	K14790SAG	1	K14791SAG	1	K14355SAG* 1
PORCELAIN WHITE	K14790WHI	1	K14791WHI	1	K14355WHIW 1
LUSTROUS WHITE	K14790LIV	1	K14791LIV	1	K14355LIVW 1
LUSTROUS BLACK	K14790LBK	1	K14791LBK	1	K14355LBKB 1
POLISHED BRASS	K14790PBR	1	K14791PBR	1	K14355PBR* 1
TEXTURED IRON	K14790TIR	1	K14791TIR	1	K14355TIRB 1
DESERT BRONZE	K14790DBZ	1	K14791DBZ	1	K14355DBZB 1
ANTIQUE BRASS	K14790ABS	1	K14791ABS	1	K14355ABSB 1
TEXTURED COPPER	K14790TCO	1	K14791TCO	1	K14355TCOB 1

LEAD TIMES: Please contact our Customer Services Department on: 01268 563 404

* Available with the option of either White or Black inserts. Add Suffix 'W' or 'B' to part number when ordering, E.g. KxxxxBSSW.

Where there is no asterix, the final suffix W = White Insert, B = Black Insert, E.g. KxxxxWHIW = Porcelain White finish with White inserts

MOUNTING BOXES:
FLUSH: 1 GANG: 866ZIC
DIMENSIONS:
102 x 86mm
FIXING CENTRES:
60.3mm
Boxes must have a
minimum depth of 35mm.

MOUNTING BOXES:
FLUSH: 2 GANG: 886ZIC
DIMENSIONS:
102 x 146mm
FIXING CENTRES:
120.6mm
Boxes must have a
minimum depth of 35mm.

MOUNTING BOX:
FLUSH 47mm: 878ZIC
DIMENSIONS:
86 x 146mm
FIXING CENTRES:
120.6mm
BS 1363 Pt 2: 1995

MOUNTING BOX:
FLUSH 46mm: 877ZIC
DIMENSIONS:
86 x 86mm
FIXING CENTRES:
60.3mm
BS EN 60669-1: 1999

Dual Earth
(see note box)