

Connection  
Units

UNSWITCHED  
FUDED

WITH NEON  
FLUSH

WITH FLEX  
OUTLET  
AND NEON  
FLUSH

DP Switches  
20 AMP

FLUSH

WITH NEON  
FLUSH

WITH FLEX  
OUTLET  
AND NEON  
FLUSH



FINISHES

BRUSHED STAINLESS STEEL	K958BSS	5	K978BSS	5	K5213BSS	5	K5233BSS	5	K5233D6BSS	5
BRUSHED CHROME	K958BRC	5	K978BRC	5	K5213BRC	5	K5233BRC	5	K5233D6BRC	5
SATIN GOLD	K958SAG	5	K978SAG	5	K5213SAG	5	K5233SAG	5	K5233D6SAG	5
POLISHED CHROME			K978PCR	5			K5233PCR	5		

MOUNTING BOXES:

FLUSH: 866ZIC

SURFACE (BRC) :  
WITH KNOCKOUTS: K899ALM

WITHOUT KNOCKOUTS:  
K829ALM

All connection units are fitted with a 13A fuse (to BS 1362)

TERMINAL CAPACITY  
2 x 6mm<sup>2</sup> stranded (max)

DIMENSIONS: 86 x 86mm

FIXING CENTRES: 60.3mm

BS 1363 Pt 4: 1995

MOUNTING BOXES:

FLUSH:  
866ZIC

SURFACE (BRC)  
WITH KNOCKOUTS:  
K899ALM

WITHOUT KNOCKOUTS:  
K829ALM

TERMINAL CAPACITY  
2 x 6mm<sup>2</sup> stranded (max)

DIMENSIONS:  
86 x 86mm

FIXING CENTRES:  
60.3mm

BS EN 60669-1: 1999

DP Switches are  
not recommended  
for switching large  
banks of PCs