

technical hotline +44 (0)1268 563720

surface | wiring devices

Euro Power Modules

Euro Datacom Modules



RJ11/12

RJ45 CAT 6

RJ45 CAT 5E



K3182WHI 1
1 GANG EURO FRONTPLATE
TWO MODULE
APERTURE SIZE 50 X 50MM

K3184WHI 1
2 GANG EURO FRONTPLATE
FOUR MODULE
APERTURE SIZE 100 X 50MM

K5830WHI 10
K5830BLK 10
UK 1 GANG EURO 2 MODULE
13A 250V SHUTTERED

K5831WHI 10
K5831BLK 10
GERMAN 2P+E
16A 250V SHUTTERED
EURO 2 MODULE (NON UK)

K5832WHI 10
K5832BLK 10
AMERICAN 2P+E
15A 127V SHUTTERED
EURO 2 MODULE (NON UK)

K5830
MOUNTING BOX: 35mm
46mm (for extra wiring space)
DIMENSIONS: 50 x 50mm
BS 1363; Pt2: 1995

K5831
MOUNTING BOX: 46mm
DIMENSIONS: 50 x 50mm
IEC 60884-1: 2006

K5832
MOUNTING BOX: 35mm
46mm (for extra wiring space)
DIMENSIONS: 50 x 50mm
SASO 2203: 2003

K5833WHI 10
K5833BLK 10
UK 1 GANG EURO 2 MODULE
5A 250V SHUTTERED

K5834WHI 10
K5834BLK 10
FRENCH/BELGIAN 2P+E
16A 250V SHUTTERED
EURO 2 MODULE (NON UK)

K5837WHI 1
K5837BLK 1
USB CHARGING MODULE
EURO 2 MODULE

K5833
MOUNTING BOX: 35mm
46mm (for extra wiring space)
DIMENSIONS: 50 x 50mm
BS 546: 1950

K5834
MOUNTING BOX: 46mm
DIMENSIONS: 50 x 50mm
NF C61-341

K5837
MOUNTING BOX: 35mm
46mm (for extra wiring space)
DIMENSIONS: 50 x 50mm

Features 2 charging sockets each delivering 1A charging current at 5Vdc (total 2A max). Allows charging of portable devices via USB 2.0 type A plug.

IEC 60950-1
IEC 61000-6-1/3

K5887WHI 5
K5887BLK 5
RJ11/12
ONE MODULE 25 X 50MM

Suitable for both RJ11 and RJ12 jacks
RJ11; 4 wire
RJ12; 6 wire

MOUNTING BOXES:
Minimum box depth 25mm

FCC68
EN 41003

K5846WHI 5
K5846BLK 5
RJ45 CAT 6
ONE MODULE 25 X 50MM

K5846sWHI 5
K5846sBLK 5
RJ45 CAT 6 SCREENED
ONE MODULE 25 X 50MM

K5864WHI 5
RJ45 CAT 6 ANGLED
ONE MODULE 25 X 50MM

Cat 6 performance.
Suitable for both 568A and 568B wiring schemes.

MOUNTING BOXES:
Minimum Box Depth 35mm

ISO/IEC 11801
EN 50173
TIA 568
EN 41003

K5844WHI 5
RJ45 CAT 5E ANGLED
ONE MODULE 25 X 50MM

K5845WHI 5
K5845BLK 5
RJ45 CAT 5E
ONE MODULE 25 X 50MM

Enhanced Cat 5 performance.
Suitable for both 568A and 568B wiring schemes.

Supplied with cable tie and cable anchors to secure wires in the connectors.

MOUNTING BOXES:
Minimum box depth 25mm standard

ISO/IEC 11801
EN 50173
TIA 568
EN 41003

Mains operated products and extra low voltage modules must not be installed within the same frontplate. Refer to BS 7671: 2008 for details.

FOR THE FULL RANGE OF EURO MODULES SEE LOGIC PLUS PAGES 54-57