

GLS BULB E27 470LM 4.8W 2700K DIMMABLE 240 BEAM FROSTED INTEGRAL

ILGLSE27DC019



This 4.8W retro-fit Integral LED Classic Globe (GLS) (large screw base) delivers a dimmable, warm light and brightness, similar to a 40W filament bulb. It features high output LEDs and an anti-glare refractor. Ideal for low level light areas such as hallways, bedrooms, cupboards or where light is always on.

Details

Quick Order Code: 642614

Barcode: 5055788202127

Category:LampsRange Name:LegacyProduct Type:GLS

Market Segment: Commercial indoor, Residential indoor

Warranty (Years): 2
CE RoHS: Yes

Physical Data

Product Length (mm): 105
Product Width (mm): 60
Product Weight (g): 30

Material: Plastic, Polycarbonate

Base Term: Edison screw

Bulb Base: E27

Construction: Aluminium and Plastic heat-sink, Injection moulded

diffuser

Globe Finish: Frosted Globe Type: GLS

Bulb Fixing: Pendant, Wall

Bulb or Luminaire Shape: Round

Placement / Application: Indoor, General Lighting

Electrical Data

Power (W): 4.8
Power Consumption (W): 4.8
Power Factor: 0.5

Wattage equivalent (W): 40
Amperage (mA): 32

Dimming: Dimmable with compatible dimmers

Driver IC Manufacturer: IWATT
Driver Included: Yes
Electric Current: AC

EN: EN-62560

LVD Certified: Yes

Light Data

Luminous Flux in Lumens (Im): 470
Luminous efficacy (Im/W): 98
Correlated Colour Temperature (CCT) (K): 2700

Colour Temperature: 2700K - Warm

Colour Temperature Name:WarmBeam Angle:240Colour Rendering Index (CRI):80

Compatible Dimmers: Varilight JQP401W

Frequency Range (Hz): 50/60
Instant on (Less than 1 second): Yes


LED Type: Surface mounted device (SMD)


Lifetime (hours): 15000 Switching Cycles: 7500

Environment

EN: EN-62560

LVD Certified: Yes
CE RoHS: Yes
Previous Energy Rating: A+
New Energy Rating: F
Hg 0% (Mercury Free): Yes
IP Rating (Ingress Protection): IP20
Lowest Operating Temperature (°C): -20
Maximum Operating Temperature (°C): 40





Packaging

Package Weight (g):	56
Package Length (mm):	120
Package Width (mm):	65
Package Depth (mm):	65
Qty per euro pallet:	1440