

GLS BULB B22 470LM 4.8W 2700K DIMMABLE 240 BEAM FROSTED INTEGRAL

ILGLSB22DC020



This 4.8W retro-fit Integral LED Classic Globe (GLS) (large bayonet base) delivers a dimmable, warm light and brightness, similar to a 40W filament bulb. It features high output LEDs and an anti-glare refractor. Ideal for low level light areas such as hallways, bedrooms, cupboards or where light is always on.

Details

Quick Order Code:	603979
Barcode:	5055788202134
Category:	Lamps
Range Name:	Legacy
Product Type:	GLS
Market Segment:	Commercial indoor, Residential indoor
Warranty (Years):	2
CE RoHS:	Yes

Physical Data

Product Length (mm):	103
Product Width (mm):	60
Product Weight (g):	78
Material:	Plastic, Polycarbonate, Nickel plated brass
Base Term:	Bayonet cap
Bulb Base:	B22
Construction:	Plastic heat-sink, Injection moulded diffuser
Globe Finish:	Frosted
Globe Type:	GLS
Bulb Fixing:	Pendant, Wall
Bulb or Luminaire Shape:	Round
Placement / Application:	Indoor, General Lighting

Electrical Data

Power (W):	4.8
Power Consumption (W) :	4.8
Power Factor:	0.5
Wattage equivalent (W):	40



Amperage (mA):	32
Dimming:	Dimmable
Driver IC Manufacturer:	IWATT
Driver Included:	Yes
Electric Current:	AC
EN:	EN-62560
LVD Certified:	Yes

Light Data

Luminous Flux in Lumens (lm):	470
Luminous efficacy (lm/W):	100
Correlated Colour Temperature (CCT) (K):	2700
Colour Temperature:	2700K - Warm
Colour Temperature Name:	Warm
Beam Angle:	240
Colour Rendering Index (CRI):	80
Compatible Dimmers:	Varilight JQP401W
Frequency Range (Hz):	50
Instant on (Less than 1 second):	Yes
LED Type:	Surface mounted device (SMD)
Lifetime (hours):	15000
Switching Cycles:	12500

Environment

EN:	EN-62560
LVD Certified:	Yes
CE RoHS:	Yes
Previous Energy Rating:	A+
New Energy Rating:	F
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	40



Portal.integral-led.com

Packaging

Product Design And Specification Subject To Change Or Modification Without Notice. Image For Illustration Only. E&OE

Package Weight (g):	56
Package Length (mm):	65
Package Width (mm):	65
Package Depth (mm):	120
Qty per euro pallet:	1200