

GLS BULB E27 1055LM 10.5W 2700K DIMMABLE 220 BEAM FROSTED INTEGRAL

ILGLSE27DC109



This 10.5W retro-fit Integral LED Classic Globe (GLS) (large screw base) delivers a cool white light and brightness, similar to a 75W filament bulb. It features high output LEDs, an anti-glare refractor, all finished in an aluminium and plastic, thermally efficient body. Ideal for living rooms, hallways and kitchens.

Details

Quick Order Code: 300420

Barcode: 5055788258902

Category:LampsRange Name:EverydayProduct Body Finish:White

Market Segment: Commercial indoor, Residential indoor

Warranty (Years): 2
CE RoHS: Yes

Physical Data

Product Length (mm): 105
Product Width (mm): 60
Product Weight (g): 31

Material: Aluminium, Polycarbonate, Nickel plated brass

Base Term: Edison screw

Bulb Base: E27

Construction: Aluminium and Plastic heat-sink, Injection moulded

diffuser

Globe Finish: Frosted
Globe Type: GLS
Bulb or Luminaire Shape: Round

Placement / Application: Indoor, General Lighting

Spot Type: SMD

Electrical Data

Power Consumption (W): 10.5
Power Factor: 0.7
Wattage equivalent (W): 75

Amperage (mA): 55

Dimming: Dimmable with compatible dimmers

Driver Included:YesElectric Current:ACTrue Wattage Eq (W):75

EN: EN-62560

LVD Certified: Yes

Light Data

Luminous Flux in Lumens (Im): 1055
Luminous efficacy (Im/W): 101
Correlated Colour Temperature (CCT) (K): 2700

Colour Temperature: 2700K - Warm

Colour Temperature Name:WarmBeam Angle:220Colour Rendering Index (CRI):80Colour Type:SingleFrequency Range (Hz):50/60Instant on (Less than 1 second):Yes


LED Type: Surface mounted device (SMD)

Lifetime (hours): 15000 Switching Cycles: 7500

Environment

EN: EN-62560

LVD Certified: Yes Yes **CE RoHS: Previous Energy Rating:** A+ F **New Energy Rating:** Hg 0% (Mercury Free): Yes **IP Rating (Ingress Protection):** IP20 **Lowest Operating Temperature (°C):** -20 **Maximum Operating Temperature (°C):** 40





Portal.integral-led.com

Package Weight (g):	190
Package Length (mm):	140
Package Width (mm):	68
Package Depth (mm):	68