

GLS BULB B22 1521LM 15W 2700K DIMMABLE 240 BEAM FROSTED INTEGRAL

ILGLSB22DC033



This 15W retro-fit Integral LED Classic Globe (GLS) (large bayonet base) delivers a dimmable, warm light and brightness. With a 1521 lumen output, this lamp is one of only a few true 100W filament bulb replacements available today. It features high output LEDs, an anti-glare refractor, all finished in an aluminium and plastic, thermally efficient body. Ideal for rooms with a single pendant fitting, living rooms, hallways and kitchens.

Details

Quick Order Code:	166464
Barcode:	5055788212621
Category:	Lamps
Range Name:	Everyday
Product Type:	GLS
Market Segment:	Commercial indoor, Residential indoor
Warranty (Years):	2
CE RoHS:	Yes

Physical Data

Product Length (mm):	120
Product Width (mm):	60
Product Weight (g):	124
Material:	Aluminium, Polycarbonate
Base Term:	Bayonet cap
Bulb Base:	B22
Construction:	Aluminium and Plastic heat-sink, Injection moulded diffuser
Globe Finish:	Frosted
Globe Type:	Classic Globe (GLS)
Bulb Fixing:	Pendant, Wall, lamp stand, table lamp
Bulb or Luminaire Shape:	Round
Placement / Application:	Indoor, General Lighting

Electrical Data

Power (W):	15
-------------------	----



Power Consumption (W) :	15
Power Factor:	0.9
Wattage equivalent (W):	100
Amperage (mA):	70
Dimming:	Dimmable
Driver IC Manufacturer:	Marvel
Driver Included:	Yes
Electric Current:	AC
EN:	EN-62560
LVD Certified:	Yes

Light Data

Luminous Flux in Lumens (lm):	1521
Luminous efficacy (lm/W):	101
Correlated Colour Temperature (CCT) (K):	2700
Colour Temperature Name:	Warm
Beam Angle:	240
Colour Rendering Index (CRI):	80
Compatible Dimmers:	Varilight JQP401W
Frequency Range (Hz):	50
Instant on (Less than 1 second):	Yes
LED Type:	Surface mounted device (SMD)
Lifetime (hours):	15000
Switching Cycles:	7500

Environment

EN:	EN-62560
LVD Certified:	Yes
CE RoHS:	Yes
Previous Energy Rating:	A+
New Energy Rating:	F
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	40



Packaging

Package Weight (g):	163
Package Length (mm):	135
Package Width (mm):	68
Package Depth (mm):	68
Qty per euro pallet:	1500

[Portal.integral-led.com](https://portal.integral-led.com)