

# CANDLE BULB B22 470LM 4.9W 2700K DIMMABLE 280 BEAM FROSTED INTEGRAL

ILCANDB22DC025



This 4.9W retro-fit Integral LED Candle (frosted finish, large bayonet, white base) delivers a dimmable, warm light and brightness, similar to a 40W filament bulb. It features high output LEDs and an anti-glare refractor. Ideal for living rooms, dining rooms, bedrooms and hotels, in classic or modern wall or floor/table lamp fittings and chandeliers.

#### **Details**

Quick Order Code: 976179

**Barcode**: 5055788202363

Category:LampsRange Name:EverydayProduct Type:Candle

Market Segment: Commercial indoor, Residential indoor

Warranty (Years): 2
CE RoHS: Yes

## **Physical Data**

Product Length (mm): 98
Product Width (mm): 35
Product Weight (g): 22

Material: Aluminium, Polycarbonate

Base Term: Bayonet cap

Bulb Base: B22

Construction: Aluminium and Plastic heat-sink, Injection moulded

diffuser

Globe Finish: Frosted Globe Type: Candle

Bulb Fixing: Pendant, Chandelier, Wall

Bulb or Luminaire Shape: Oval

Placement / Application: Indoor, General Lighting

#### **Electrical Data**

Power (W): 4.9 Power Consumption (W): 4.9 Power Factor: 0.7
Wattage equivalent (W): 40
Amperage (mA): 30

**Dimming:** Dimmable with compatible dimmers

Driver IC Manufacturer: IWATT
Driver Included: Yes
Electric Current: AC

**EN:** EN-62560

LVD Certified: Yes

### **Light Data**

Luminous Flux in Lumens (Im): 470
Luminous efficacy (Im/W): 96
Correlated Colour Temperature (CCT) (K): 2700

Colour Temperature: 2700K - Warm

Colour Temperature Name:WarmBeam Angle:280Colour Rendering Index (CRI):80

Compatible Dimmers: Varilight JQP401W

Frequency Range (Hz): 50/60
Instant on (Less than 1 second): Yes


**LED Type:** Surface mounted device (SMD)


Lifetime (hours): 15000 Switching Cycles: 7500

#### **Environment**

**EN:** EN-62560

LVD Certified: Yes **CE RoHS:** Yes **Previous Energy Rating:** A+ **New Energy Rating:** F Hg 0% (Mercury Free): Yes IP20 **IP Rating (Ingress Protection):** Lowest Operating Temperature (°C): -20 **Maximum Operating Temperature (°C):** 40





# **Packaging**

Package Weight (g): 49
Package Length (mm): 110
Package Width (mm): 50
Package Depth (mm): 50
Qty per euro pallet: 2880