

**MPN:** 6944LSH-120.0

**Product Name:** 6944LSH 120.0mm<sup>2</sup> Black XLPE/SWA/Basec Cable 4-Core 1m

**Brand:** Commodity Cables

**Category:** Steel Wire Armoured (SWA)

---

**Product Description:** This product is cut to specification. Hence when ordering, a multiple of 1 needs to be entered.

---

#### **Key Features:**

- Cable Size: 120.0mm<sup>2</sup>
- Number of cores: 4
- CPR Compliant
- BASEC-Approved
- Material: LSHF

---

## Specifications:

- Conductor Operating Temperature up to 90 °C
- Conductor Short Circuit Temperature up to 250 °C
- Flame Retardant acc. to BS EN 60332-3-24
- Smoke emission acc. to BS EN 61034
- Acid gas emission acc. to BS EN 60754
- Conductor Max. DC Resistance at 20°C : 0.153 Ω/km
- Conductor Max. AC Resistance at 90°C: 0.1964 Ω/km
- Reactance at 50 Hz: 0.0708 Ω/km
- Conductor Short Circuit Current for 1 second: 17.2 kA
- Rated Current (laid in Air) \*: 393 A
- Rated Current (laid in Duct) \*: 301 A
- Rated Current (laid in Ground) \*: 397 A
- Conductor: Circular Stranded Compacted Plain Annealed Copper (Class 2)
- Insulation: XLPE (GP 8)
- Inner Sheath: LSHF
- Nominal Cable Diameter: 45.1mm

---

## ETIM Class-9.0: Power cable < 1 kV, for flexible applications (EC003250)

---


## Applications:

- For outdoor and indoor fixed installations and it's normally used for power distribution in urban networks and industrial plants.
- Suitable for laying underground directly or in ducts or on trays in free air.
- Industrial automation systems for control and instrumentation circuits
- Renewable energy projects such as solar farms and wind power installations
- Marine and offshore applications including shipbuilding and offshore platforms.
- Transportation infrastructure projects like railway networks, subway systems, and airports

---

## Standards:

- BS 6724
- BS EN 60228



Unlock exclusive deals and discover a world of innovative solutions by scanning our QR code and visiting Rexel's website today!