




MPN: 6944XLH-25.0

Product Name: 6944XLH 25.0mm² Black PVC XLPE/SWA/Basec Cable 4-Core 1m

Brand: Commodity Cables

Category: Steel Wire Armoured (SWA)

Product Description: This product is cut to specification. Hence when ordering, a multiple of 1 needs to be entered.

Key Features:

- Cable Size: 25.0mm²
- No. of cores: 4
- CPR Compliant
- BASEC-Approved
- Material: PVC

Specifications:

- Conductor Operating Temp. up to 90 °C
- Conductor Short Circuit Temp. up to 250 °C
- Conductor Max. DC Resistance at 20°C 0.727 Ω/km
- Conductor Max. AC Resistance at 90°C 0.9273 Ω/km
- Conductor Short Circuit Current for 1 sec. 3.6Ka
- Rated Current (laid in Air) * 136A
- Rated Current (laid in Duct) * 116A
- Rated Current (laid in Ground) * 154A
- Conductor: 25 mm² Circular Stranded Compacted Annealed Copper (Class 2)
- Filling: Polypropylene Filler
- Insulation: XLPE (GP 8)
- Armour: Steel Wire Armour
- Tape: Binder Tape
- Nominal Cable Diameter: 27.5mm

ETIM Class-9.0: Power cable < 1 kV, for fixed installations (EC003248)

Applications:

- For outdoor and indoor fixed installations and it's normally used for power distribution in urban networks and industrial plants.
- Suitable for laying underground directly or in ducts or on trays in free air.
- Industrial automation systems for control and instrumentation circuits
- Renewable energy projects such as solar farms and wind power installations
- Marine and offshore applications including shipbuilding and offshore platforms.
- Transportation infrastructure projects like railway networks, subway systems, and airports

Standards:

- BS 6724
- BS EN 60228



Unlock exclusive deals and discover a world of innovative solutions by scanning our QR code and visiting Rexel's website today!